

Safety data sheet according to WHS Regulations

Printing date 21.03.2016

Vers.-Nr: 41



Revision: 21.03.2016

Hazardous according to criteria of Australian Safety and Compensation Council

1 Identification

- **Product identifier**
- **Trade name: Transothane Finish 3.63 HS base**
- **Article number:** 363HS-a
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance/preparation:** Paint
- **Details of the supplier of the safety data sheet**
- **Manufacturer/supplier:**
Transocean Coatings
Wagon Paints Australia Pty Ltd
ABN: 76 412 791 772
Street address: 5 Stephenson Road, Bayswater North
VIC, 3153 Australia
Phone: +613 9729-1344
Fax: +613 9720 2719
- **Emergency telephone number:**
Manufacturer/Supplier
(03) 9729 1344 from 8.00 am to 4.30 pm.

2 Hazard Identification

- **Classification of the substance or mixture**
Flam. Liq. 3 H226 Flammable liquid and vapour.
Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.
- **Label elements**
- **GHS label elements**
The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**

GHS02 GHS07
- **Signal word** Warning
- **Hazard-determining components of labelling:**
xylene, mixture of isomers
ethylbenzene
- **Hazard statements**
Flammable liquid and vapour.
Harmful if inhaled.
Causes skin irritation.
- **Precautionary statements**
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.

(Contd. on page 2)

Safety data sheet according to WHS Regulations

Printing date 21.03.2016

Vers.-Nr: 41

Revision: 21.03.2016

Trade name: Transothane Finish 3.63 HS base

(Contd. of page 1)

Avoid breathing dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Specific treatment (see on this label).

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition and information on ingredients

- **Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

1330-20-7	xylene, mixture of isomers ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	10-25%
14808-60-7	Quartz (SiO ₂)	10-25%
100-41-4	ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332	2,5-10%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First Aid Measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire Fighting Measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet

(Contd. on page 3)

Safety data sheet according to WHS Regulations

Printing date 21.03.2016

Vers.-Nr: 41

Revision: 21.03.2016

Trade name: Transothane Finish 3.63 HS base

(Contd. of page 2)

- **Special hazards arising from the substance or mixture**
No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 xylene, mixture of isomers

NES	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 350 mg/m ³ , 80 ppm
-----	--

14808-60-7 Quartz (SiO₂)

NES	Long-term value: 0.1 mg/m ³ respirable dust
-----	---

(Contd. on page 4)

Safety data sheet according to WHS Regulations

Printing date 21.03.2016

Vers.-Nr: 41

Revision: 21.03.2016

Trade name: Transothane Finish 3.63 HS base

(Contd. of page 3)

100-41-4 ethylbenzene

NES	Short-term value: 543 mg/m ³ , 125 ppm Long-term value: 434 mg/m ³ , 100 ppm
-----	---

· DNELs

1330-20-7 xylene, mixture of isomers

Dermal	long term DNEL	108 mg/kg/d (General Population) 180 mg/kg/d (Workers)
Inhalative	long term DNEL	14.8 mg/m ³ (General Population) 77 mg/m ³ (Workers)

· PNECs

1330-20-7 xylene, mixture of isomers

PNEC STP	6.58 mg/l (water treatment plant)
PNEC aqua	327 ug/l (freshwater) 327 ug/l (marine water)
PNEC sediment	12.46 mg/kg (freshwater) 12.46 mg/kg (marine water)
PNEC soil	2.31 mg/kg (Soil)

· **Additional information:** The lists valid during the making were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Safety data sheet according to WHS Regulations

Printing date 21.03.2016

Vers.-Nr: 41

Revision: 21.03.2016

Trade name: Transothane Finish 3.63 HS base

(Contd. of page 4)

- **Penetration time of glove material**
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Fluid
Colour: According to product specification

- **Odour:** Characteristic
- **Odour threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Boiling point/Boiling range: 137 °C

- **Flash point:** 25 °C

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 500 °C

- **Decomposition temperature:** Not determined.

- **Self-igniting:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- **Explosion limits:**

Lower: 1.1 Vol %
Upper: 7.0 Vol %

- **Vapour pressure at 20 °C:** 6.7 hPa

- **Density at 20 °C:** 1.26158 g/cm³
- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

Dynamic at 20 °C: 2000 mPas
Kinematic: Not determined.

(Contd. on page 6)

Safety data sheet according to WHS Regulations

Printing date 21.03.2016

Vers.-Nr: 41

Revision: 21.03.2016

Trade name: Transothane Finish 3.63 HS base

(Contd. of page 5)

- **Solvent content:**
VOC (EC) 331.9 g/l
- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

- **LD/LC50 values relevant for classification:**

1330-20-7 xylene, mixture of isomers

Oral	LD50	>2000 mg/kg (rat)
	LC50/ 96 hr (static)	2.6 mg/l (Rainbow trout (<i>Oncorhynchus mykiss</i>)) (OESO 203 or equivalent)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>20 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Irritant to skin and mucous membranes.
- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Irritant

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

1330-20-7 xylene, mixture of isomers

EC 50 (48 hr)	1-10 mg/l (daphnia)
EC 50 (72 hr)	1-10 mg/l (Algae)

- **Persistence and degradability** No further relevant information available.

(Contd. on page 7)

Safety data sheet according to WHS Regulations

Printing date 21.03.2016

Vers.-Nr: 41

Revision: 21.03.2016

Trade name: Transothane Finish 3.63 HS base


(Contd. of page 6)

- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	Void
· ADG, ADN, IMDG	Void
· IATA	UN1993
· UN proper shipping name	Void
· ADG, ADN, IMDG	Void
· IATA	Flammable liquid, n.o.s. (Xylenes, ethylbenzene)
· Transport hazard class(es)	
· ADG, ADN, IMDG	
· Class	Void
· IATA	
	
· Class	3 Flammable liquids.
· Label	3
· Packing group	
· ADG, IMDG	Void
· IATA	III

(Contd. on page 8)

Safety data sheet according to WHS Regulations

Printing date 21.03.2016

Vers.-Nr: 41

Revision: 21.03.2016

Trade name: Transothane Finish 3.63 HS base

(Contd. of page 7)

- | | |
|---|-----------------|
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · UN "Model Regulation": | Void |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Australian Inventory of Chemical Substances**

13463-67-7	titanium dioxide
1330-20-7	xylene, mixture of isomers
14808-60-7	Quartz (SiO ₂)
100-41-4	ethylbenzene
77-58-7	dibutyltin dilaurate
108-65-6	2-methoxy-1-methylethyl acetate
123-86-4	n-butyl acetate
1333-86-4	Carbon black

- **Standard for the Uniform Scheduling of Medicines and Poisons**

1330-20-7	xylene, mixture of isomers	S6
-----------	----------------------------	----

- **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning

- **Hazard-determining components of labelling:**

xylene, mixture of isomers
ethylbenzene

- **Hazard statements**

Flammable liquid and vapour.
Harmful if inhaled.
Causes skin irritation.

- **Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
Avoid breathing dust/fume/gas/mist/vapours/spray.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

(Contd. on page 9)

Safety data sheet according to WHS Regulations

Printing date 21.03.2016

Vers.-Nr: 41

Revision: 21.03.2016

Trade name: Transothane Finish 3.63 HS base

(Contd. of page 8)

Specific treatment (see on this label).

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P5c FLAMMABLE LIQUIDS**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

- *** Data compared to the previous version altered.**