

Safety data sheet according to WHS Regulations

Printing date 21.03.2016

Vers.-Nr: 56


Revision: 21.03.2016

Hazardous according to criteria of Australian Safety and Compensation Council

1 Identification

- **Product identifier**
- **Trade name: Transozinc Epoxy Primer 1.55 pack A**
- **Article number:** 155a-3
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance/preparation:**
Epoxy coating
Paint
- **Details of the supplier of the safety data sheet**
- **Manufacturer/supplier:**
Transocean Coatings
Wagon Paints Australia Pty Ltd
ABN: 76 412 791 772
Street address: 5 Stephenson Road, Bayswater North
VIC, 3153 Australia
Phone: +613 9729-1344
Fax: +613 9720 2719
- **Emergency telephone number:**
Manufacturer/Supplier
(03) 9729 1344 from 8.00 am to 4.30 pm.

2 Hazard Identification

- **Classification of the substance or mixture**
Flam. Liq. 2 H225 Highly flammable liquid and vapour.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Dam. 1 H318 Causes serious eye damage.
Skin Sens. 1 H317 May cause an allergic skin reaction.
- **Label elements**
- **GHS label elements**
The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**

GHS02 GHS05 GHS07
- **Signal word** Danger
- **Hazard-determining components of labelling:**
xylene, mixture of isomers
iso-butanol
reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight > 700)
4-methylpentan-2-one

(Contd. on page 2)

Safety data sheet according to WHS Regulations

Printing date 21.03.2016

Vers.-Nr: 56

Revision: 21.03.2016

Trade name: Transozinc Epoxy Primer 1.55 pack A

(Contd. of page 1)

- **Hazard statements**
Highly flammable liquid and vapour.
Causes skin irritation.
Causes serious eye damage.
May cause an allergic skin reaction.
- **Precautionary statements**
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER/doctor.
Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition and information on ingredients

- **Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

| | | |
|------------|---|---------|
| 1330-20-7 | xylene, mixture of isomers ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 | 2,5-10% |
| 25036-25-3 | reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight > 700) ⚠ Skin Sens. 1, H317 | 2,5-10% |
| 67-63-0 | propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336 | 2,5-10% |
| 78-83-1 | iso-butanol ⚠ Flam. Liq. 3, H226; ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; STOT SE 3, H335-H336 | 2,5-10% |
| 108-10-1 | 4-methylpentan-2-one ⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335 | ≤ 2,5% |

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First Aid Measures

- **Description of first aid measures**
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 3)

Safety data sheet according to WHS Regulations

Printing date 21.03.2016

Vers.-Nr: 56

Revision: 21.03.2016

Trade name: Transozinc Epoxy Primer 1.55 pack A

(Contd. of page 2)

- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

* 5 Fire Fighting Measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

* 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

* 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Use only in well ventilated areas.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.

(Contd. on page 4)

Safety data sheet according to WHS Regulations

Printing date 21.03.2016

Vers.-Nr: 56

Revision: 21.03.2016

Trade name: Transozinc Epoxy Primer 1.55 pack A

(Contd. of page 3)

- Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 xylene, mixture of isomers

| | |
|-----|--|
| NES | Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 350 mg/m ³ , 80 ppm |
|-----|--|

67-63-0 propan-2-ol

| | |
|-----|--|
| NES | Short-term value: 1230 mg/m ³ , 500 ppm Long-term value: 983 mg/m ³ , 400 ppm |
|-----|--|

78-83-1 iso-butanol

| | |
|-----|---|
| NES | Long-term value: 152 mg/m ³ , 50 ppm |
|-----|---|

108-10-1 4-methylpentan-2-one

| | |
|-----|---|
| NES | Short-term value: 307 mg/m ³ , 75 ppm Long-term value: 205 mg/m ³ , 50 ppm |
|-----|---|

· **DNELs**

7440-66-6 zinc powder -zinc dust (stabilized)

| | | |
|------------|----------------|-------------------------------|
| Inhalative | long term DNEL | 5 mg/m ³ (Workers) |
|------------|----------------|-------------------------------|

- **Additional information:** The lists valid during the making were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has

(Contd. on page 5)

Safety data sheet according to WHS Regulations

Printing date 21.03.2016

Vers.-Nr: 56

Revision: 21.03.2016

Trade name: Transozinc Epoxy Primer 1.55 pack A

(Contd. of page 4)

therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Fluid
Colour: According to product specification

- **Odour:** Characteristic

- **Odour threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Boiling point/Boiling range: 82 °C

- **Flash point:** 13 °C

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 425 °C

- **Decomposition temperature:** Not determined.

- **Self-igniting:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- **Explosion limits:**

Lower: Not determined.

Upper: Not determined.

- **Vapour pressure:** Not determined.

- **Density at 20 °C:** 2.61825 g/cm³

- **Relative density** Not determined.

- **Vapour density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

water: Not miscible or difficult to mix.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

Dynamic at 20 °C: 1500 mPas

(Contd. on page 6)

Safety data sheet according to WHS Regulations

Printing date 21.03.2016

Vers.-Nr: 56

Revision: 21.03.2016

Trade name: Transozinc Epoxy Primer 1.55 pack A

(Contd. of page 5)

| | |
|----------------------------|--|
| Kinematic: | Not determined. |
| · Solvent content: | |
| VOC (EC) | 464.5 g/l |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

- **LD/LC50 values relevant for classification:**

7440-66-6 zinc powder -zinc dust (stabilized)

| | | |
|------------|--------------------|--------------------|
| Oral | LD50 | > 2000 mg/kg (rat) |
| Inhalative | LC50/4 h (dynamic) | 5.4 mg/l (rat) |

- **Primary irritant effect:**
- **Skin corrosion/irritation** Irritant to skin and mucous membranes.
- **Serious eye damage/irritation** Irritating effect.
- **Respiratory or skin sensitisation** Sensitisation possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Very toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 7)

Safety data sheet according to WHS Regulations

Printing date 21.03.2016

Vers.-Nr: 56

Revision: 21.03.2016

Trade name: Transozinc Epoxy Primer 1.55 pack A

(Contd. of page 6)

Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Very toxic for aquatic organisms

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· **ADG, IMDG, IATA**

UN1263

· **UN proper shipping name**

· **ADG**

1263 PAINT, ENVIRONMENTALLY HAZARDOUS,
special provision 640H

· **IMDG**

PAINT (zinc powder -zinc dust (stabilized)),
MARINE POLLUTANT

· **IATA**

Paint

· **Transport hazard class(es)**

· **ADG, IATA**



· **Class**

3 Flammable liquids.

· **Label**

3

· **IMDG**



· **Class**

3 Flammable liquids.

· **Label**

3

· **Packing group**

· **ADG, IMDG, IATA**

III

(Contd. on page 8)

Safety data sheet according to WHS Regulations

Printing date 21.03.2016

Vers.-Nr: 56

Revision: 21.03.2016

Trade name: Transozinc Epoxy Primer 1.55 pack A

(Contd. of page 7)

| | |
|---|--|
| · Environmental hazards: | Product contains environmentally hazardous substances: |
| · Marine pollutant: | Yes Symbol (fish and tree) |
| · Special precautions for user | Warning: Flammable liquids. |
| · Danger code (Kemler): | - |
| · EMS Number: | F-E, S-E |
| · Stowage Category | A |
| · Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · ADG | |
| · Limited quantities (LQ) | 5L |
| · Excepted quantities (EQ) | Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| · Transport category | 3 |
| · Tunnel restriction code | E |
| · IMDG | |
| · Limited quantities (LQ) | 5L |
| · Excepted quantities (EQ) | Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| · UN "Model Regulation": | UN 1263 PAINT, SPECIAL PROVISION 640H, 3, III, ENVIRONMENTALLY HAZARDOUS |

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Australian Inventory of Chemical Substances**

| | |
|------------|--|
| 1330-20-7 | xylene, mixture of isomers |
| 25036-25-3 | reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weigh > 700) |
| 67-63-0 | propan-2-ol |
| 78-83-1 | iso-butanol |
| 108-10-1 | 4-methylpentan-2-one |
| 1318-02-1 | Crystalline aluminosilicate |
| 1309-37-1 | Red iron oxide |
| | Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl) dimethyl, chlorides, compds. with hectorite |
| | Synthetic amorphous, pyrogenic silica |

· **Standard for the Uniform Scheduling of Medicines and Poisons**

| | | |
|-----------|----------------------------|----|
| 1330-20-7 | xylene, mixture of isomers | S6 |
|-----------|----------------------------|----|

(Contd. on page 9)

Safety data sheet according to WHS Regulations

Printing date 21.03.2016

Vers.-Nr: 56

Revision: 21.03.2016

Trade name: Transozinc Epoxy Primer 1.55 pack A

(Contd. of page 8)

108-10-1 4-methylpentan-2-one

S5

· **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02 GHS05 GHS07

· **Signal word** Danger

· **Hazard-determining components of labelling:**

xylene, mixture of isomers

iso-butanol

reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight > 700)

4-methylpentan-2-one

· **Hazard statements**

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye damage.

May cause an allergic skin reaction.

· **Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category**

E1 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 100 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

(Contd. on page 10)

Safety data sheet according to WHS Regulations

Printing date 21.03.2016

Vers.-Nr: 56

Revision: 21.03.2016

Trade name: Transozinc Epoxy Primer 1.55 pack A

(Contd. of page 9)

EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Flam. Liq. 3: Flammable liquids, Hazard Category 3
Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

• *** Data compared to the previous version altered.**

AU