



# Safety Data Sheet

## Hazardous Substance, Dangerous Goods

### 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

**Product name:** Rhinofloor HBE Accelerator

**Recommended use:** Used to improve the rate of cure of Epoxy coatings, particularly at Low temperatures..

**Supplier:** Wagon Paints Australia Pty Ltd

**ABN:** 76 412 791 772

**Street Address:** 5 Stephenson Road Bayswater North VIC 3153 Australia

**Telephone:** +613 9729-1344

**Facsimile:** +613 9720 2179

**Emergency Telephone number:** (03) 9729 1344 from 8:00 am to 4:30 pm

### 2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.



#### Signal Word

Warning

#### Hazard Classifications

Skin irritation - Category 2

Eye irritation - category 2

Acute toxicity - category 4 (Oral)

#### Hazard Statements

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation

#### Prevention Precautionary Statements

P261 Avoid breathing dust, fume, gas, mist, vapours or spray.

P264 Wash hands face and all exposed skin thoroughly after handling.

P280 Wear protective clothing, gloves, eye/face protection and suitable respirator.

#### Response Precautionary Statements

P301 + P330 + P331 If swallowed: Rinse mouth, do not induce vomiting.

P303 + P361 + P353 If on skin (or hair): Remove/take off immediately all contaminated clothing.

Rinse skin with water/shower.

P304 + P340 + P310 If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

P305 + P351 + P338 + P310 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse

**Product Name:** Rhinofloor HBE Accelerator

**Version:** 1.0

**Issued:** 10/07/17

**Page** 1 of 8



# Safety Data Sheet

## Storage Precautionary Statements

P403+P233+P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool.

## Disposal Precautionary Statement

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

**Poison Schedule:** Not Applicable

## DANGEROUS GOOD CLASSIFICATION

Classified as dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous good by Road or rail" and the "New Zealand NZS5433: Transport of Dangerous Good on Land"

**Dangerous Goods Class:** 8

### 3. COMPOSITION INFORMATION

Ingredients	CAS NO	Basis
Ethanol	64-17-5	AU OEL
Propylene glycol	57-55-6	AU OEL

### 4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

**Inhalation:** Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

**Skin Contact:** If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; or for 15 minutes and transport to Doctor or Hospital. For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble).

For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

**Eye contact:** If in eyes wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

**Ingestion:** Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

**Notes to physician:** Treat symptomatically. Effects may be delayed.

**Suitable extinguishing media:** Use an extinguishing agent suitable for the surrounding fire.

**Hazchem Code:** 3W



# Safety Data Sheet

## 5. FIRE FIGHTING MEASURES

**Specific hazards:** In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Fire fighting further advice:** On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

## 6. ACCIDENTAL RELEASE MEASURES

### Methods and material for containment and cleaning up:

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

**Dangerous Goods Initial Emergency Response Guide No: 8A1**

## 7. HANDLING AND STORAGE

**Handling:** Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols.

**Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Store locked up. Keeps container standing upright. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Class 8 Corrosive as per the criteria of the “Australian Code for the Transport of Dangerous Goods by Road & Rail” and/or the “New Zealand NZS5433: Transport of Dangerous Goods on Land” and must be stored in accordance with the relevant regulations.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

CAS-No	Value type	STEL	Concentration	Basis
64-17-5	TWA	1.000 ppm	1.880 mg/m <sup>3</sup>	ACGIH
57-55-6	TWA	1.000 ppm	10.mg/m <sup>3</sup>	AU CEL

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

Sk Notice - absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.



# Safety Data Sheet

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

**Biological Limit Values:** As per the "National model regulations for the control of workplace hazardous substances (Safe Work Australia)" The ingredients in this material do not have a Biological Limit Allocated.

**Engineering Measures:** Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Use with local exhaust ventilation or while wearing appropriate respirator. Vapour heavier than air - prevent concentration in hollows or sumps. Do NOT enter confined spaces where vapour may have collected.

**Personal Protection Equipment:** SAFETY SHOES, OVERALLS, GLOVES, CHEMICAL GOGGLES, RESPIRATOR. Wear safety shoes, overalls, gloves, chemical goggles, respirator. Use with adequate ventilation.

If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact.

However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Hygiene measures:** Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Form:** Liquid

**Colour:** Light yellow

**Odour:** Alcoholic

**Solubility:** Partially soluble in water(20°C)

**Specific Gravity (25 °C):** Approx. 1.17

**Relative Vapour Density (air=1):** >1

**Vapour Pressure (KPa):** 0.1 @ 20 °C

**Flash Point (19°C)**

**Flammability Limits (%):** N App

**Autoignition Temperature (°C):** N App

**Melting Point/Range (°C):** N Av

**Boiling Point/Range (66°C)**

**pH:** 5.6 concentration 500g/l (20°C)

**Viscosity:** 10-100 mpa.s (25°C)

**Total VOC (g/Litre):** N Av

(Typical values only - consult specification sheet)

N Av = Not available, N App = Not applicable



# Safety Data Sheet

## 10. STABILITY AND REACTIVITY

**Chemical stability:** This material is thermally stable when stored and used as directed.

**Conditions to avoid:** Elevated temperatures and sources of ignition.

**Incompatible materials:** Incompatible with strong acids & bases, strong oxidising agents.

**Hazardous decomposition products:** Oxides of carbon, smoke and other toxic fumes.

**Hazardous reactions:** No known hazardous reactions.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

### Acute Effects

**Inhalation:** Material may be an irritant to mucous membranes and respiratory tract. Inhalation of vapour can result in headaches, dizziness and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness.

**Skin contact:** Contact with skin will result in irritation. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

**Ingestion:** Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

**Eye contact:** May cause serious eye damage.

### Acute toxicity

**Inhalation:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >20 mg/L

**Skin contact:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): Acute toxicity estimate (based on ingredients): > 2,000 mg/Kg

**Ingestion:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg

**Corrosion/Irritancy:** Eye: this material has been classified as SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1. Skin: this material has been classified as a Category 2 Hazard (reversible effects to skin).

**Sensitisation:** Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as a Category 1 Hazard (skin sensitiser).

**Aspiration hazard:** This material has been classified as non-hazardous.

**Specific target organ toxicity (single exposure):** This material has been classified as non-hazardous.



# Safety Data Sheet

## Chronic Toxicity

**Mutagenicity:** This material has been classified as non-hazardous.

**Carcinogenicity:** This material has been classified as non-hazardous.

**Reproductive toxicity (including via lactation):** This material has been classified as non-hazardous.

**Specific target organ toxicity (repeat exposure):** This material has been classified as non-hazardous.

## 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

**Acute aquatic hazard:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >100 mg/L

**Long-term aquatic hazard:** This material has been classified as non-hazardous. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log  $K_{ow}$  < 4.

**Ecotoxicity:** No information available.

**Persistence and degradability:** No information available.

**Bioaccumulative potential:** No information available.

**Mobility:** No information available.

## 13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see Section 8. "Exposure Controls/ Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

## 14. TRANSPORT INFORMATION

### ROAD AND RAIL TRANSPORT



Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of dangerous Goods by Road or Rail and the New Zealand NZS5433: Transport of dangerous Goods on Land



# Safety Data Sheet

**Packing Group:** III

**UN No:** 1993

**Dangerous Goods Class:** 3

**Hazchem Code:** 3YE

**Emergency Response Guide** 8A1

**Proper Shipping Name:** Ethanol, Calcium Nitrate (flammable Liquid, N.O.S.)

**Segregation Dangerous Goods:** Not to be loaded with explosives (Class 1), dangerous when wet, (Class 4.3), oxidising agents (Class 5.1), organic peroxides (Class 5.2), or radioactive substances (Class 7). Exemptions may apply.

## MARINE TRANSPORT



Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. This material is classified as a Marine Pollutant (P) according to the International Maritime Dangerous Goods Code.

**Packing Group:** III

**UN No:** 27

**Dangerous Goods Class:** 8 Corrosive

**Emergency Response Guide** 8A1

**Proper Shipping Name:** Polyalkyl amines, corrosive, N.O.S.

## AIR TRANSPORT



Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

**Packing Group:** III

**UN No:** 27

**Dangerous Goods Class:** 8 Corrosive

**Emergency Response Guide** 8A1

**Proper Shipping Name:** Polyalkyl amines, corrosive, N.O.S.

## 15. REGULATORY INFORMATION

**This material is not subject to the following international agreements:**

Montreal Protocol (Ozone depleting substances)  
The Stockholm Convention (Persistent Organic Pollutants)  
The Rotterdam Convention (Prior Informed Consent)  
Basel Convention (Hazardous Waste)

**This material is subject to the following international agreements:**

Basel Convention (Hazardous Waste)  
Wastes from production, formulation and use of resins, latex, plasticizers, glues/adhesives



# Safety Data Sheet

**This material/constituent(s) is covered by the following requirements:**

All components of this product are listed on or exempt from the Australian Inventory of Chemical Substances (AICS).

All components of this product are listed on or exempt from the New Zealand Inventory of Chemical (NZIoC) .

**HSNO Group Standard:** HSR002658 – Surface Coatings and Colourants (Corrosive) Group Standard 2006

## 16. OTHER INFORMATION

Reason for issue: Update to GHS SDS standard.

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.



