



T18 Enamel Retarder Thinner

Code: THT180000

Description

- Slow thinner used in conjunction with T9 and T4 for reducing baking enamels to spray viscosity

Properties

- Slows initial flash off to provide better flow
- Reduces occurrence of solvent boil

Typical Applications

- Additional thinning of Baking Enamel and Baking Epoxy Enamel when use of T9 or T4 alone is too fast

General Data

- Specially formulated blend of hydrocarbon solvents

Specifications (at 25°C and 50% relative humidity)

- Appearance..... Low viscosity, clear, water-white liquid
- Specific Gravity.....0.87
- Boiling Range..... 155 - 175°C

Mixing recommendation

- Add in 1% increments, by volume, and spray test before further addition
- Use up to 5% maximum

Safety precautions

- **Refer to the relevant Material Safety Data Sheet**
- Contents are flammable – keep away from all ignition sources
- Avoid contact with skin and eyes – when mixing, wear gloves and goggles
- When spraying, ensure adequate ventilation and wear appropriate protective clothing and equipment

Packaging Group III UN No. 1263

Pack sizes 4 litre, 20 litre

Authorised: A. De Mello, Sales Manager

June 2008

These technical data and recommendations are based on tests and information believed to be accurate at the time of printing. They should not be construed as containing any warranty, either expressed or implied. Users should conduct their own tests to determine final suitability of this product.



Wagon Paints

5 Stephenson Road, Bayswater North, Victoria 3153 Australia
Phone: 61 3 97291344 Fax: 61 3 97202179 Email: sales@wagonpaints.com.au