



T24 Acetone

Code: THT240000

Description

- Solvent for clean up of Polyester products and air-dry enamels

Properties

- Very strong solvency

Typical Applications

- Suitable for clean up of polyester gelcoat and flowcoat resins
- Also effective for cleaning application equipment used with air-dry enamels

General Data

- Commercial acetone

Specifications (at 25°C and 50% relative humidity)

- Appearance..... Low viscosity, clear, water-white liquid
- Specific Gravity..... 0.8
- Boiling Range..... 56°C

Mixing recommendation

- Apply liberal amounts of T24 and scrub equipment with a stiff bristle brush immediately after use of polyester resins and enamel paint products

Safety precautions

- **Refer to the relevant Material Safety Data Sheet**
- Contents are flammable – keep away from all ignition sources
- Avoid contact with skin and eyes – when mixing, wear gloves and goggles
- When spraying, ensure adequate ventilation and wear appropriate protective clothing and equipment

Packaging Group II **UN No. 1090**

Pack sizes 1 litre, 4 litre, 20 litre, 60 litre, 200 litre

Authorised: A. De Mello, Sales Manager

June 2008

These technical data and recommendations are based on tests and information believed to be accurate at the time of printing. They should not be construed as containing any warranty, either expressed or implied. Users should conduct their own tests to determine final suitability of this product.



Wagon Paints

5 Stephenson Road, Bayswater North, Victoria 3153 Australia
Phone: 61 3 97291344 Fax: 61 3 97202179 Email: sales@wagonpaints.com.au