

## Safety Data Sheet according to WHS Regulations

Printing date 01.04.2021

Vers.-Nr: 55


Revision: 01.04.2021

Hazardous according to criteria of Australian Safety and Compensation Council.

### 1 Identification

- **Product identifier**
- **Trade name: Transpoxy Intermediate 2.19 pack A**
- **Article number:** 219a
- **Registration number** APVMA approval Number: 84506
- **Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance/preparation:**  
Epoxy coating  
Paint
- **Details of the supplier of the safety data sheet**
- **Manufacturer/supplier:**  
Transocean Coatings  
Wagon Paints Australia Pty Ltd  
ABN: 76 412 791 772  
Street address: 5 Stephenson Road, Bayswater North  
VIC, 3153 Australia  
Phone: +613 9729-1344  
Fax: +613 9720 2719
- **Emergency telephone number:**  
Manufacturer/Supplier  
(03) 9729 1344 from 8.00 am to 4.30 pm.

### 2 Hazard(s) Identification

- **Classification of the substance or mixture**  
Flam. Liq. 3 H226 Flammable liquid and vapour.  
Skin Irrit. 2 H315 Causes skin irritation.  
Eye Irrit. 2A H319 Causes serious eye irritation.  
Skin Sens. 1 H317 May cause an allergic skin reaction.  
Carc. 2 H351 Suspected of causing cancer.
- **Label elements**
- **GHS label elements**  
The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**  
  
GHS02 GHS07 GHS08
- **Signal word** Warning
- **Hazard-determining components of labelling:**  
reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weigh > 700)  
4-methylpentan-2-one

(Contd. on page 2)

## Safety Data Sheet according to WHS Regulations

Printing date 01.04.2021

Vers.-Nr: 55

Revision: 01.04.2021

**Trade name: Transpoxy Intermediate 2.19 pack A**

(Contd. of page 1)

**Hazard statements**

- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.

**Precautionary statements**

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Other hazards**
**Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition and Information on Ingredients

**Chemical characterisation: Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

|            |  |           |
|------------|--|-----------|
| 25036-25-3 | reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weigh > 700)<br>⚠ Skin Sens. 1, H317         | 10-25%    |
| 1330-20-7  | xylene, mixture of isomers<br>⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H335 | ≥10-<20%  |
| 64742-95-6 | Hydrocarbons, C9, aromatics<br>⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H335-H336                                   | 2.5-10%   |
| 108-10-1   | 4-methylpentan-2-one<br>⚠ Flam. Liq. 2, H225; ⚠ Carc. 2, H351; ⚠ Acute Tox. 4, H332; Eye Irrit. 2A, H319; STOT SE 3, H335          | ≥2.5-<10% |
| 12001-26-2 | Mica   | 2.5-10%   |
| 67-63-0    | propan-2-ol<br>⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2A, H319; STOT SE 3, H336  | ≤2.5%     |
| 107-98-2   | 1-methoxy-2-propanol<br>⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336  | ≤2.5%     |

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

AU

(Contd. on page 3)

## Safety Data Sheet according to WHS Regulations

Printing date 01.04.2021

Vers.-Nr: 55

Revision: 01.04.2021

Trade name: Transpoxy Intermediate 2.19 pack A

(Contd. of page 2)

### 4 First Aid Measures

- **Description of first aid measures**
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire Fighting Measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

### 6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and Storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.

(Contd. on page 4)

## Safety Data Sheet according to WHS Regulations

Printing date 01.04.2021

Vers.-Nr: 55

Revision: 01.04.2021

**Trade name: Transpoxy Intermediate 2.19 pack A**

(Contd. of page 3)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**1330-20-7 xylene, mixture of isomers**

|     |  |
|-----|--|
| WES | Short-term value: 655 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 350 mg/m <sup>3</sup> , 80 ppm |
|-----|--|

**108-10-1 4-methylpentan-2-one**

|     |   |
|-----|---|
| WES | Short-term value: 307 mg/m <sup>3</sup> , 75 ppm<br>Long-term value: 205 mg/m <sup>3</sup> , 50 ppm |
|-----|---|

**12001-26-2 Mica**

|     |  |
|-----|--|
| WES | Long-term value: 2.5 mg/m <sup>3</sup> |
|-----|--|

**67-63-0 propan-2-ol**

|     |  |
|-----|--|
| WES | Short-term value: 1230 mg/m <sup>3</sup> , 500 ppm<br>Long-term value: 983 mg/m <sup>3</sup> , 400 ppm |
|-----|--|

**107-98-2 1-methoxy-2-propanol**

|     |   |
|-----|---|
| WES | Short-term value: 553 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 369 mg/m <sup>3</sup> , 100 ppm |
|-----|---|

· **DNELs**

**1330-20-7 xylene, mixture of isomers**

|            |                |   |
|------------|----------------|---|
| Dermal     | long term DNEL | 108 mg/kg/d (General Population)            |
|            |                | 180 mg/kg/d (Workers)                       |
| Inhalative | long term DNEL | 14.8 mg/m <sup>3</sup> (General Population) |
|            |                | 77 mg/m <sup>3</sup> (Workers)              |

**64742-95-6 Hydrocarbons, C9, aromatics**

|            |                |   |
|------------|----------------|---|
| Oral       | long term DNEL | 11 mg/kg/d (General Population)           |
| Dermal     | long term DNEL | 11 mg/kg/d (General Population)           |
|            |                | 25 mg/kg/d (Workers)                      |
| Inhalative | long term DNEL | 32 mg/m <sup>3</sup> (General Population) |
|            |                | 150 mg/m <sup>3</sup> (Workers)           |

**67-63-0 propan-2-ol**

|            |                |                                  |
|------------|----------------|----------------------------------|
| Oral       | long term DNEL | 26 mg/kg/d (General Population)  |
| Dermal     | long term DNEL | 319 mg/kg/d (General Population) |
|            |                | 888 mg/kg/d (Workers)            |
| Inhalative | long term DNEL | 500 mg/m <sup>3</sup> (Workers)  |

(Contd. on page 5)

## Safety Data Sheet according to WHS Regulations

Printing date 01.04.2021

Vers.-Nr: 55

Revision: 01.04.2021

**Trade name: Transpoxy Intermediate 2.19 pack A**

(Contd. of page 4)

### 107-98-2 1-methoxy-2-propanol

|            |                |   |
|------------|----------------|---|
| Oral       | long term DNEL | 3.3 mg/kg/d (General Population)            |
| Dermal     | long term DNEL | 18.1 mg/kg/d (General Population)           |
| Inhalative | long term DNEL | 50.6 mg/kg/d (Workers)                      |
|            |                | 43.9 mg/m <sup>3</sup> (General Population) |
|            | Acute DNEL     | 369 mg/m <sup>3</sup> (Workers)             |
|            |                | 553.5 mg/m <sup>3</sup> (Workers)           |

#### · PNECs

### 1330-20-7 xylene, mixture of isomers

|               |                                   |
|---------------|-----------------------------------|
| PNEC STP      | 6.58 mg/l (water treatment plant) |
| PNEC aqua     | 327 ug/l (freshwater)             |
|               | 327 ug/l (marine water)           |
| PNEC sediment | 12.46 mg/kg (freshwater)          |
|               | 12.46 mg/kg (marine water)        |
| PNEC soil     | 2.31 mg/kg (Soil)                 |

### 67-63-0 propan-2-ol

|               |                                   |
|---------------|-----------------------------------|
| PNEC STP      | 2251 mg/l (water treatment plant) |
| PNEC aqua     | 140009 ug/l (freshwater)          |
|               | 140009 ug/l (marine water)        |
| PNEC sediment | 552 mg/kg (freshwater)            |
|               | 552 mg/kg (marine water)          |

### 107-98-2 1-methoxy-2-propanol

|               |                                  |
|---------------|----------------------------------|
| PNEC STP      | 100 mg/l (water treatment plant) |
| PNEC aqua     | 10000 ug/l (freshwater)          |
| PNEC sediment | 41.6 mg/kg (freshwater)          |
|               | 4.17 mg/kg (marine water)        |
| PNEC soil     | 2.47 mg/kg (Soil)                |

· **Additional information:** The lists valid during the making were used as basis.

#### · Exposure controls

#### · Personal protective equipment:

#### · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 6)

## Safety Data Sheet according to WHS Regulations

Printing date 01.04.2021

Vers.-Nr: 55

Revision: 01.04.2021

**Trade name: Transpoxy Intermediate 2.19 pack A**

(Contd. of page 5)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

### 9 Physical and Chemical Properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid  
Colour: According to product specification

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 114 °C

· **Flash point:** 26 °C

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 450 °C

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower: 1.1 Vol %

Upper: 7 Vol %

· **Vapour pressure at 20 °C:** 6.7 hPa

· **Density at 20 °C:** 1.45482 g/cm<sup>3</sup>

· **Relative density** Not determined.

· **Vapour density** Not determined.

(Contd. on page 7)

## Safety Data Sheet

### according to WHS Regulations

Printing date 01.04.2021

Vers.-Nr: 55

Revision: 01.04.2021

**Trade name: Transpoxy Intermediate 2.19 pack A**

(Contd. of page 6)

|  |  |
|--|--|
| · <b>Evaporation rate</b>                        | Not determined.                            |
| · <b>Solubility in / Miscibility with water:</b> | Not miscible or difficult to mix.          |
| · <b>Partition coefficient: n-octanol/water:</b> | Not determined.                            |
| · <b>Viscosity:</b>                              |  |
| <b>Dynamic:</b>                                  | Not determined.                            |
| <b>Kinematic:</b>                                | Not determined.                            |
| · <b>Solvent content:</b>                        |  |
| <b>VOC (EC)</b>                                  | 467.4 g/l                                  |
| · <b>Other information</b>                       | No further relevant information available. |

## 10 Stability and Reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological Information

- **Information on toxicological effects**
- **Acute toxicity**

- **LD/LC50 values relevant for classification:**

**25036-25-3 reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight > 700)**

|            |          |                      |
|------------|----------|----------------------|
| Oral       | LD50     | >2000 mg/kg (rat)    |
| Dermal     | LD50     | >2000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | >4000 mg/l (rat)     |

**1330-20-7 xylene, mixture of isomers**

|            |                      |   |
|------------|----------------------|---|
| Oral       | LD50                 | >2000 mg/kg (rat)   |
|            | LC50/ 96 hr (static) | 2.6 mg/l (Rainbow trout (Oncorhynchus mykiss)) (OESO 203 or equivalent) |
| Dermal     | LD50                 | >2000 mg/kg (rabbit)  |
| Inhalative | LC50/4 h             | >20 mg/l (rat)  |

**64742-95-6 Hydrocarbons, C9, aromatics**

|            |             |  |
|------------|-------------|--|
| Oral       | LD50        | 3492 mg/kg (rat)                               |
|            | LC50/ 96 hr | 9.2 mg/l (Rainbow trout (Oncorhynchus mykiss)) |
| Dermal     | LD50        | >3160 mg/kg (rab)                              |
| Inhalative | LC50/4 h    | >6193 mg/l (rat)                               |

(Contd. on page 8)

## Safety Data Sheet according to WHS Regulations

Printing date 01.04.2021

Vers.-Nr: 55

Revision: 01.04.2021

**Trade name: Transpoxy Intermediate 2.19 pack A**

(Contd. of page 7)

**108-10-1 4-methylpentan-2-one**

|            |          |                     |
|------------|----------|---------------------|
| Oral       | LD50     | 2080 mg/kg (rat)    |
| Dermal     | LD50     | 16000 mg/kg (rab)   |
| Inhalative | LC50/4 h | 8.3-16.6 mg/l (rat) |

**67-63-0 propan-2-ol**

|            |             |                      |
|------------|-------------|----------------------|
| Oral       | LD50        | 5045 mg/kg (rat)     |
|            | LC50/ 96 hr | 9640 mg/l (fish)     |
| Dermal     | LD50        | 12800 mg/kg (rabbit) |
| Inhalative | LC50/4 h    | 30 mg/l (rat)        |

**107-98-2 1-methoxy-2-propanol**

|            |             |                     |
|------------|-------------|---------------------|
| Oral       | LD50        | 4016 mg/kg (rat)    |
|            | LC50/ 96 hr | 6812 mg/l (fish)    |
| Dermal     | LD50        | 2000 mg/kg (rabbit) |
| Inhalative | LC50/4 h    | 6 mg/l (rat)        |

- **Primary irritant effect:**
- **Skin corrosion/irritation** Irritant to skin and mucous membranes.
- **Serious eye damage/irritation** Irritating effect.
- **Respiratory or skin sensitisation** Sensitisation possible through skin contact.
- **Additional toxicological information:**  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Irritant

**12 Ecological Information**

· **Toxicity**

· **Aquatic toxicity:**

**1330-20-7 xylene, mixture of isomers**

|               |                     |
|---------------|---------------------|
| EC 50 (48 hr) | 1-10 mg/l (daphnia) |
| EC 50 (72 hr) | 1-10 mg/l (Algae)   |

**64742-95-6 Hydrocarbons, C9, aromatics**

|               |                    |
|---------------|--------------------|
| EC 50 (48 hr) | 3.2 mg/l (daphnia) |
| EC 50 (72 hr) | 2.9 mg/l (Algae)   |

**67-63-0 propan-2-ol**

|               |                      |
|---------------|----------------------|
| EC50          | >1000 mg/l (daphnia) |
| EC 50 (72 hr) | >1000 mg/l (Algae)   |

**107-98-2 1-methoxy-2-propanol**

|               |                      |
|---------------|----------------------|
| EC 50 (48 hr) | 23300 mg/l (daphnia) |
|---------------|----------------------|

- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxic effects:**
- **Remark:** Harmful to fish

(Contd. on page 9)



## Safety Data Sheet according to WHS Regulations

Printing date 01.04.2021

Vers.-Nr: 55

Revision: 01.04.2021

**Trade name: Transpoxy Intermediate 2.19 pack A**


(Contd. of page 8)

- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>· <b>UN-Number</b></li> <li>· <b>ADG, IMDG, IATA</b></li> </ul>   | <p style="margin-left: 20px;">UN1263</p>   |
| <ul style="list-style-type: none"> <li>· <b>UN proper shipping name</b></li> <li>· <b>ADG</b></li> <li>· <b>IMDG, IATA</b></li> </ul>  | <p style="margin-left: 20px;">1263 PAINT<br/>PAINT</p>   |
| <ul style="list-style-type: none"> <li>· <b>Transport hazard class(es)</b></li> <li>· <b>ADG, IMDG, IATA</b></li> </ul>  | <div style="text-align: center; margin-bottom: 10px;">  </div> <p style="margin-left: 20px;">3 Flammable liquids.<br/>3</p> |
| <ul style="list-style-type: none"> <li>· <b>Packing group</b></li> <li>· <b>ADG, IMDG, IATA</b></li> </ul>   | <p style="margin-left: 20px;">III</p>  |
| <ul style="list-style-type: none"> <li>· <b>Environmental hazards:</b></li> <li>· <b>Marine pollutant:</b></li> </ul>  | <p style="margin-left: 20px;">No</p>   |
| <ul style="list-style-type: none"> <li>· <b>Special precautions for user</b></li> <li>· <b>Hazard identification number (Kemler code):</b></li> <li>· <b>EMS Number:</b></li> <li>· <b>Stowage Category</b></li> </ul> | <p style="margin-left: 20px;">Warning: Flammable liquids.<br/>30<br/>F-E,S-E<br/>A</p>   |

(Contd. on page 10)

## Safety Data Sheet according to WHS Regulations

Printing date 01.04.2021

Vers.-Nr: 55

Revision: 01.04.2021

**Trade name: Transpoxy Intermediate 2.19 pack A**

(Contd. of page 9)

|   |  |
|---|--|
| <b>· Transport in bulk according to Annex II of Marpol and the IBC Code</b> | Not applicable.  |
| <b>· Transport/Additional information:</b>                                  |  |
| <b>· ADG</b>  |  |
| · Limited quantities (LQ)   | 5L   |
| · Excepted quantities (EQ)  | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| · Transport category  | 3  |
| · Tunnel restriction code   | D/E  |
| <b>· IMDG</b>   |  |
| · Limited quantities (LQ)   | 5L   |
| · Excepted quantities (EQ)  | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| · UN "Model Regulation":  | UN 1263 PAINT, 3, III  |

### 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Australian Inventory of Industrial Chemicals**

|            |  |
|------------|--|
| 14807-96-6 | Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )                                    |
| 25036-25-3 | reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weigh > 700)         |
| 13463-67-7 | titanium dioxide   |
| 1330-20-7  | xylene, mixture of isomers   |
| 108-10-1   | 4-methylpentan-2-one   |
| 12001-26-2 | Mica   |
| 67-63-0    | propan-2-ol  |
| 107-98-2   | 1-methoxy-2-propanol   |
| 67762-90-7 | Reaction product of dimethyl silicones with silica.  |
| 64-17-5    | ethanol  |
|            | Quaternary ammonium compounds,benzyl(hydrogenated tallow alkyl) dimethyl,chlorides, compds. with hectorite |

· **Standard for the Uniform Scheduling of Medicines and Poisons**

|           |                            |    |
|-----------|----------------------------|----|
| 1330-20-7 | xylene, mixture of isomers | S6 |
| 108-10-1  | 4-methylpentan-2-one       | S5 |

· **Australia: Priority Existing Chemicals**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

(Contd. on page 11)

## Safety Data Sheet according to WHS Regulations

Printing date 01.04.2021

Vers.-Nr: 55

Revision: 01.04.2021

**Trade name: Transpoxy Intermediate 2.19 pack A**

(Contd. of page 10)

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Warning

· **Hazard-determining components of labelling:**

reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight > 700)

4-methylpentan-2-one

· **Hazard statements**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category** P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5000 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50000 t

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Contact:**

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 12)

## Safety Data Sheet according to WHS Regulations

Printing date 01.04.2021

Vers.-Nr: 55

Revision: 01.04.2021

**Trade name: Transpoxy Intermediate 2.19 pack A**

(Contd. of page 11)

ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
VOC: Volatile Organic Compounds (USA, EU)  
DNEL: Derived No-Effect Level (REACH)  
PNEC: Predicted No-Effect Concentration (REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Liq. 2: Flammable liquids – Category 2  
Flam. Liq. 3: Flammable liquids – Category 3  
Acute Tox. 4: Acute toxicity - dermal – Category 4  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A  
Skin Sens. 1: Skin sensitisation – Category 1  
Carc. 2: Carcinogenicity – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
Asp. Tox. 1: Aspiration hazard – Category 1

· \* **Data compared to the previous version altered.**

AU