



# T6 MEK

Code: THT60000

## Description

- Secondary thinner for reducing specialized coatings to application viscosity

## Properties

- Very fast initial flash-off
- High solvency

## Typical Applications

- Refer to Wagon Paints' Technical department

## General Data

- Commercial methyl ethyl ketone

## Specifications (at 25°C and 50% relative humidity)

- Appearance.....Low viscosity, clear, water-white liquid
- Specific Gravity.....0.80
- Boiling Range.....79 - 80°C

## Mixing recommendation

- Refer to Wagon Paints' Technical department

## Safety precautions

- **Refer to the relevant Material Safety Data Sheet**
- Contents are flammable – keep away from all ignition sources
- Avoid contact with skin and eyes – when mixing, wear gloves and goggles
- When spraying, ensure adequate ventilation and wear appropriate protective clothing and equipment

**Packaging Group II**      **UN No. 1193**

**Pack sizes**      4 litre, 20 litre, 60 litre

Authorised:      A. De Mello, Sales Manager

June 2008

These technical data and recommendations are based on tests and information believed to be accurate at the time of printing. They should not be construed as containing any warranty, either expressed or implied. Users should conduct their own tests to determine final suitability of this product.



Wagon Paints

5 Stephenson Road, Bayswater North, Victoria 3153 Australia  
Phone: 61 3 97291344 Fax: 61 3 97202179 Email: sales@wagonpaints.com.au