

Safety data sheet according to WHS Regulations

Printing date 01.04.2021

Vers.-Nr: 46



Revision: 01.04.2021

Hazardous according to criteria of Australian Safety and Compensation Council

1 Identification

- **Product identifier**
- **Trade name:** Transothane Finish 3.63 Pack B
- **Article number:** 363b
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance/preparation:** Paint
- **Details of the supplier of the safety data sheet**
- **Manufacturer/supplier:**
Transocean Coatings
Transocean Coatings Prins
Hendrikkade 12c 3071 KB
Rotterdam Phone: +31-0(10)-
4134477 Info@transocean-
coatings.com www.transocean-
coatings.com Wagon Paints
Australia Pty Ltd ABN: 76 412
791 772
Street address: 5 Stephenson Road, Bayswater
North VIC, 3153 Australia
Phone: +613 9729-1344
Fax: +613 9720 2719
- **Emergency telephone number:**
Manufacturer/Supplier
(03) 9729 1344 from 8.00 am to 4.30 pm.

2 Hazard Identification

- **Classification of the substance or mixture**
Flam. Liq. 3 H226 Flammable liquid and vapour.
Skin Irrit. 2 H315 Causes skin irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
- **Label elements**
- **GHS label elements**
The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**

GHS02 GHS07
- **Signal word** Warning
- **Hazard-determining components of labelling:**
xylene, mixture of isomers
Aliphatic Isocyanate
ethylbenzene

(Contd. on page 2)

Safety data sheet according to WHS Regulations

Printing date 01.04.2021

Vers.-Nr: 46

Revision: 01.04.2021

Trade name: Transothane Finish 3.63 Pack B

(Contd. of page 1)

- hexamethylene-di-isocyanate
- **Hazard statements**
 - Flammable liquid and vapour.
 - Causes skin irritation.
 - May cause an allergic skin reaction.
- **Precautionary statements**
 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - Use explosion-proof electrical/ventilating/lighting/equipment.
 - Avoid breathing dust/fume/gas/mist/vapours/spray.
 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 - Specific treatment (see on this label).
 - Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition and information on ingredients

- **Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

• **Dangerous components:**

28182-81-2	Aliphatic Isocyanate ⚠ Skin Sens. 1, H317	50-100%
1330-20-7	xylene, mixture of isomers ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	25-50%
108-65-6	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	2,5-10%
100-41-4	ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332	≤ 2,5%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First Aid Measures

- **Description of first aid measures**
- **General information:**
 - Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
 - Supply fresh air and to be sure call for a doctor.
 - In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.

(Contd. on page 3)

Safety data sheet according to WHS Regulations

Printing date 01.04.2021

Vers.-Nr: 46

Revision: 01.04.2021

Trade name: Transothane Finish 3.63 Pack B

(Contd. of page 2)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire Fighting Measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 4)

Safety data sheet according to WHS Regulations

Printing date 01.04.2021

Vers.-Nr: 46

Revision: 01.04.2021

Trade name: Transothane Finish 3.63 Pack B

(Contd. of page 3)

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 xylene, mixture of isomers

NES Short-term value: 655 mg/m³, 150 ppm
Long-term value: 350 mg/m³, 80 ppm

108-65-6 2-methoxy-1-methylethyl acetate

NES Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk

100-41-4 ethylbenzene

NES Short-term value: 543 mg/m³, 125 ppm
Long-term value: 434 mg/m³, 100 ppm

822-06-0 hexamethylene-di-isocyanate

NES Short-term value: 0.07 mg/m³
Long-term value: 0.02 mg/m³
Sen, as -NCO

· **DNELs**

1330-20-7 xylene, mixture of isomers

Dermal	long term DNEL	108 mg/kg/d (General Population) 180 mg/kg/d (Workers)
Inhalative	long term DNEL	14.8 mg/m ³ (General Population) 77 mg/m ³ (Workers)

· **PNECs**

1330-20-7 xylene, mixture of isomers

PNEC STP	6.58 mg/l (water treatment plant)
PNEC aqua	327 ug/l (freshwater) 327 ug/l (marine water)
PNEC sediment	12.46 mg/kg (freshwater) 12.46 mg/kg (marine water)
PNEC soil	2.31 mg/kg (Soil)

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:** Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

Safety data sheet according to WHS Regulations

Printing date 01.04.2021

Vers.-Nr: 46

Revision: 01.04.2021

Trade name: Transothane Finish 3.63 Pack B

(Contd. of page 4)

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic

Odour threshold:	Not determined.
-------------------------	-----------------

pH-value:	Not determined.
------------------	-----------------

· **Change in condition**

Boiling point/Boiling range:	137 °C
-------------------------------------	--------

Flash point:	30 °C
---------------------	-------

Flammability (solid, gaseous):	Not applicable.
---------------------------------------	-----------------

Ignition temperature:	315 °C
------------------------------	--------

Decomposition temperature:	Not determined.
-----------------------------------	-----------------

Self-igniting:	Product is not selfigniting.
-----------------------	------------------------------

Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
-----------------------------	---

(Contd. on page 6)

Safety data sheet according to WHS Regulations

Printing date 01.04.2021

Vers.-Nr: 46

Revision: 01.04.2021

Trade name: Transothane Finish 3.63 Pack B

(Contd. of page 5)

· Explosion limits:	
Lower:	1.1 Vol %
Upper:	10.8 Vol %
· Vapour pressure at 20 °C: 6.7 hPa	
· Density at 20 °C: 1.023 g/cm ³	
· Relative density Not determined.	
· Vapour density Not determined.	
· Evaporation rate Not determined.	
· Solubility in / Miscibility with water: Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water): Not determined.	
· Viscosity:	
Dynamic at 20 °C:	600 mPas
Kinematic:	Not determined.
· Solvent content:	
VOC (EC)	409.2 g/l
· Other information No further relevant information available.	

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

· **LD/LC50 values relevant for classification:**

1330-20-7 xylene, mixture of isomers

Oral	LD50	>2000 mg/kg (rat)
	LC50/ 96 hr (static)	2.6 mg/l (Rainbow trout (<i>Oncorhynchus mykiss</i>)) (OESO 203 or equivalent)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>20 mg/l (rat)

822-06-0 hexamethylene-di-isocyanate

Oral	LD50	738 mg/kg (rat)
Dermal	LD50	593 mg/kg (rat)

(Contd. on page 7)

Safety data sheet according to WHS Regulations

Printing date 01.04.2021

Vers.-Nr: 46

Revision: 01.04.2021

Trade name: Transothane Finish 3.63 Pack B

(Contd. of page 6)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Irritant to skin and mucous membranes.
- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** Sensitisation possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Irritant

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

1330-20-7 xylene, mixture of isomers

EC 50 (48 hr) 1-10 mg/l (daphnia)

EC 50 (72 hr) 1-10 mg/l (Algae)

- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **ADG, ADN, IMDG** Void
- **IATA** UN1993

(Contd. on page 8)

Safety data sheet according to WHS Regulations


Printing date 01.04.2021

Vers.-Nr: 46

Revision: 01.04.2021

Trade name: Transothane Finish 3.63 Pack B

(Contd. of page 7)

<ul style="list-style-type: none"> · UN proper shipping name · ADG, ADN, IMDG · IATA 	<p>Void</p> <p>Flammable liquid, n.o.s. (Xylenes, ethylbenzene)</p>
<ul style="list-style-type: none"> · Transport hazard class(es) · ADG, ADN, IMDG · Class 	<p>Void</p>
<ul style="list-style-type: none"> · IATA 	
	
<ul style="list-style-type: none"> · Class · Label 	<p>3 Flammable liquids.</p> <p>3</p>
<ul style="list-style-type: none"> · Packing group · ADG, IMDG · IATA 	<p>Void</p> <p>III</p>
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: 	<p>No</p>
<ul style="list-style-type: none"> · Special precautions for user 	<p>Not applicable.</p>
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of Marpol and the IBC Code 	<p>Not applicable.</p>
<ul style="list-style-type: none"> · UN "Model Regulation": 	<p>Void</p>

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Australian Inventory of Chemical Substances**

All ingredients are listed.

- **Standard for the Uniform Scheduling of Medicines and Poisons**

1330-20-7 xylene, mixture of isomers

S6

- **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning

- **Hazard-determining components of labelling:**

xylene, mixture of isomers
Aliphatic Isocyanate

(Contd. on page 9)

Safety data sheet according to WHS Regulations

Printing date 01.04.2021

Vers.-Nr: 46

Revision: 01.04.2021

Trade name: Transothane Finish 3.63 Pack B

(Contd. of page 8)

ethylbenzene

hexamethylene-di-isocyanate

• **Hazard statements**

Flammable liquid and vapour.

Causes skin irritation.

May cause an allergic skin reaction.

• **Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Avoid breathing dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Specific treatment (see on this label).

Dispose of contents/container in accordance with local/regional/national/international regulations.

• **Directive 2012/18/EU**

• **Named dangerous substances - ANNEX I** None of the ingredients is listed.

• **Seveso category** P5c FLAMMABLE LIQUIDS

• **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

• **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

• *** Data compared to the previous version altered.**