

Safety data sheet

according to WHS Regulations Vers.-Nr: 41 Printing date 01.04.2021 Revision: 01.04.2021 Hazardous according to criteria of Australian Safety and Compensation Council **1** Identification · Product identifier Trade name: Transothane Finish 3.63 HS Pack A · Article number: 363HS-a · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance/preparation: Paint · Details of the supplier of the safety data sheet · Manufacturer/supplier: Transocean Coatings Wagon Paints Australia Pty Ltd ABN: 76 412 791 772 Street address: 5 Stephenson Road, Bayswater North VIC, 3153 Australia Phone: +613 9729-1344 Fax: +613 9720 2719 · Emergency telephone number: Manufacturer/Supplier (03) 9729 1344 from 8.00 am to 4.30 pm. **2 Hazard Identification**

· Classification of the substance or mixture

Flam. Lig. 3 H226 Flammable liquid and vapour. Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Label elements

· GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS). · Hazard pictograms



· Signal word Warning

- · Hazard-determining components of labelling: xylene, mixture of isomers ethylbenzene · Hazard statements
- Flammable liquid and vapour. Harmful if inhaled. Causes skin irritation.
- · Precautionary statements Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical/ventilating/lighting/equipment.

(Contd. on page 2)



Page 2/9

Printing date 01.04.2021

Vers.-Nr: 41

Revision: 01.04.2021

Trade name: Transothane Finish 3.63 HS Pack A

(Contd. of page 1)

Avoid breathing dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

Specific treatment (see on this label).

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Other hazards

· Results of PBT and vPvB assessment

- · PBT: Not applicable.
- · **vPvB:** Not applicable.

3 Composition and information on ingredients

· Chemical characterisation: Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

	xylene, mixture of isomers Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin — — Irrit. 2, H315	10-25%		
14808-60-7	Quartz (SiO2)	10-25%		
	ethylbenzene 🍝 Flam. Liq. 2, H225; 🔹 STOT RE 2, H373; Asp. Tox. 1, H304; 🕂 Acute Tox. 4, H332	2,5-10%		
····· · · · · · · · · · · · · · · · ·				

· Additional information: For the wording of the listed risk phrases refer to section 16.

4 First Aid Measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- \cdot For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 3)

AU



Vers.-Nr: 41

(Contd. of page 2)

Revision: 01.04.2021

Trade name: Transothane Finish 3.63 HS Pack A

• Special hazards arising from the substance or mixture No further relevant information available.

· Advice for firefighters

Printing date 01.04.2021

• Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- \cdot Information about fire and explosion protection:

Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

• Information about storage in one common storage facility: Not required.

- Further information about storage conditions: Keep container tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· Control parameters

· Ingredients with limit values that require monitoring at the workplace:

1330-20-7 xylene, mixture of isomers

NES Short-term value: 655 mg/m³, 150 ppm

Long-term value: 350 mg/m³, 80 ppm

14808-60-7 Quartz (SiO2)

NES Long-term value: 0.1 mg/m³

respirable dust

(Contd. on page 4)



Printing date 01.04.2021

Vers.-Nr: 41

Revision: 01.04.2021

Trade name: Transothane Finish 3.63 HS Pack A

100-41-4	ethylb	enzene	(Contd. of page
	-		mg/m³, 125 ppm
			mg/m ³ , 100 ppm
DNELs			
1330-20-7	xylen	e, mixture	of isomers
Dermal	-		108 mg/kg/d (General Population)
			180 mg/kg/d (Workers)
Inhalative	long t	erm DNEL	14.8 mg/m3 (General Population)
			77 mg/m3 (Workers)
PNECs			
	-		of isomers
PNEC STI		U V	water treatment plant)
PNEC aqu	la	327 ug/l (fr	
			narine water)
PNEC sec	liment	-	(g (freshwater)
		-	kg (marine water)
PNEC soil		2.31 mg/kg	
Additiona	l infor	mation: Th	e lists valid during the making were used as basis.
Exposure			
		tive equip	nent: gienic measures: Keep
			ages and feed. Immediately
			ninated clothing Wash hands
		d at the end	
		ses / fumes	/ aerosols.
Avoid cont		h the skin.	and skin
Respirato			
In case of exposure	brief e use se	xposure or lf-contained	low pollution use respiratory filter device. In case of intensive or longer respiratory protective device.
Protection	n of ha	inds:	
	Protec	tive gloves	
The glove preparatio		al has to be	e impermeable and resistant to the product/ the substance/ the
Due to mis	ssing te	ests no reco	mmendation to the glove material can be given for the product/ the

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

AU



Printing date 01.04.2021

Vers.-Nr: 41

Revision: 01.04.2021

Trade name: Transothane Finish 3.63 HS Pack A

(Contd. of page 4)

• **Penetration time of glove material** The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

Information on basic physical and che	emical properties
· General Information	
· Appearance: Form:	Fluid
Form: Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
	Not determined.
· pH-value:	Not determined.
 Change in condition 	
Boiling point/Boiling range:	137 °C
· Flash point:	25 ℃
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	500 °C
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.0 Vol %
· Vapour pressure at 20 °C:	6.7 hPa
· Density at 20 °C:	1.26158 g/cm ³
· Relative density	Not determined.
· Vapour density ·	Not determined.
Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water)	Not determined.
· Viscosity:	
Dynamic at 20 °C:	2000 mPas
Kinematic:	Not determined.
	(Contd. on page 6

AU



Printing date 01.04.2021

Vers.-Nr: 41

Revision: 01.04.2021

(Contd. of page 5)

Trade name: Transothane Finish 3.63 HS Pack A

- Solvent content:
- VOC (EC)

· Other information

331.9 g/l No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

· LD/LC50 values relevant for classification:

1330-20-7 xylene, mixture of isomers			
Oral	LD50	>2000 mg/kg (rat)	
	LC50/ 96 hr (static)	2.6 mg/I (Rainbow trout (Oncorhynchus mykiss)) (OESO 203 or	
		equivalent)	
Dermal	LD50	>2000 mg/kg (rabbit)	
Inhalative	LC50/4 h	>20 mg/l (rat)	

- · Primary irritant effect:
- Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Serious eye damage/irritation No irritating effect.
- Respiratory or skin sensitisation No sensitising effects known.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Harmful Irritant

12 Ecological information

- Toxicity
- Aquatic toxicity:
- 1330-20-7 xylene, mixture of isomers
- EC 50 (48 hr) 1-10 mg/l (daphnia)
- EC 50 (72 hr) 1-10 mg/l (Algae)
- Persistence and degradability No further relevant information available.

(Contd. on page 7)

AU



IS Regulations

Vers.-Nr: 41 Revision: 01.04.2021

Trade name: Transothane Finish 3.63 HS Pack A

(Contd. of page 6)

- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Printing date 01.04.2021

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

UN-Number	
ADG, ADN, IMDG	Void
ΙΑΤΑ	UN1993
UN proper shipping name	
ADG, ADN, IMDG	Void
ΙΑΤΑ	Flammable liquid, n.o.s. (Xylenes, ethylbenzene)
Transport hazard class(es)	
ADG, ADN, IMDG	
Class	Void
ΙΑΤΑ	
Class	3 Flammable liquids.
Label	3
Packing group	
ADG, IMDG	Void
IATA	III





Printing date 01.04.2021 Vers.-Nr: 41 Revision: 01.04.2021

Trade name: Transothane Finish 3.63 HS Pack A

		(Contd. of page 7)
 Environmental hazards: Marine pollutant: 	No	
 Special precautions for user 	Not applicable.	
 Transport in bulk according to Anne Marpol and the IBC Code 	x II of Not applicable.	
· UN "Model Regulation":	Void	

15 Regulatory information

 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Chemical Substances				
13463-67-7	titanium dioxide			
1330-20-7	xylene, mixture of isomers			
14808-60-7	Quartz (SiO2)			
	ethylbenzene			
77-58-7	dibutyltin dilaurate			
108-65-6	2-methoxy-1-methylethyl acetate			
123-86-4	n-butyl acetate			
1333-86-4	Carbon black			
Standard for the Uniform Scheduling of Medicines and Poisons				
1330-20-7	cylene, mixture of isomers	S6		

- GHS label elements
- The product is classified and labelled according to the Globally Harmonised System (GHS).
- Hazard pictograms



- · Signal word Warning
- Hazard-determining components of labelling: xylene, mixture of isomers ethylbenzene
- Hazard statements
 Flammable liquid and vapour.
 Harmful if inhaled.
 Causes skin irritation.
- · Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical/ventilating/lighting/equipment. Avoid breathing dust/fume/gas/mist/vapours/spray. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

(Contd. on page 9)



Page 9/9

Safety data sheet according to WHS Regulations

Printing date 01.04.2021

Vers.-Nr: 41

Revision: 01.04.2021

Trade name: Transothane Finish 3.63 HS Pack A

Specific treatment (see on this label).

(Contd. of page 8)

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids, Hazard Category 2 Flam. Liq. 3: Flammable liquids, Hazard Category 3 Acute Tox. 4: Acute toxicity, Hazard Category 4 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2 Asp. Tox. 1: Aspiration hazard, Hazard Category 1 • * Data compared to the previous version altered.