



Printing date 01.04.2021 Vers.-Nr: 50 Revision: 01.04.2021

Hazardous according to criteria of Australian Safety and Compensation Council

1 Identification

- · Product identifier
- · Trade name: Transpoxy Masterbond 4.67 N Pack A
- · Article number: 467a
- \cdot Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance/preparation:

Epoxy coating

Paint

- · Details of the supplier of the safety data sheet
- · Manufacturer/supplier:

Transocean Coatings

Transocean Coatings Prins

Hendrikkade 12c 3071 KB

Rotterdam Phone: +31-0(10)-

4134477 Info@transocean-

coatings.com www.transocean-

coatings.com Wagon Paints

Australia Pty Ltd ABN: 76 412

791 772

Street address: 5 Stephenson Road, Bayswater

North VIC, 3153 Australia Phone: +613 9729-1344 Fax: +613 9720 2719

· Emergency telephone number:

Manufacturer/Supplier

(03) 9729 1344 from 8.00 am to 4.30 pm.

2 Hazard Identification

· Classification of the substance or mixture

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms





GHS02 GHS07

· Signal word Warning

(Contd. on page 2)



Printing date 01.04.2021 Vers.-Nr: 50 Revision: 01.04.2021

Trade name: Transpoxy Masterbond 4.67 N Pack A

(Contd. of page 1)

· Hazard-determining components of labelling:

xylene, mixture of isomers

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weigh > 700)

Benzyl alcohol

· Hazard statements

Flammable liquid and vapour.

Causes skin irritation. Causes

serious eye irritation.

May cause an allergic skin reaction.

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical/ventilating/lighting/equipment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition and information on ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous	components:	
14808-60-7	Quartz (SiO2)	10-25%
	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700) Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	10-25%
25036-25-3	reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weigh > 700) Skin Sens. 1, H317	10-25%
1330-20-7	xylene, mixture of isomers Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	2,5-10%
100-51-6	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332	2,5-10%
107-98-2	1-methoxy-2-propanol Flam. Liq. 3, H226; STOT SE 3, H336	≤ 2,5%

• Additional information: For the wording of the listed risk phrases refer to section 16.





Printing date 01.04.2021 Vers.-Nr: 50 Revision: 01.04.2021

Trade name: Transpoxy Masterbond 4.67 N Pack A

(Contd. of page 2)

4 First Aid Measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- $\boldsymbol{\cdot}$ Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

No further relevant information available.

- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

(Contd. on page 4)





Printing date 01.04.2021 Vers.-Nr: 50 Revision: 01.04.2021

Trade name: Transpoxy Masterbond 4.67 N Pack A

(Contd. of page 3)

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

14808-60-7 Quartz (SiO2)

NES Long-term value: 0.1 mg/m³

respirable dust

1330-20-7 xylene, mixture of isomers NES

Short-term value: 655 mg/m³, 150 ppm

Long-term value: 350 mg/m³, 80 ppm

107-98-2 1-methoxy-2-propanol

NES Short-term value: 553 mg/m³, 150 ppm

Long-term value: 369 mg/m³, 100 ppm

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eves and skin.
- Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of

(Contd. on page 5)





Printing date 01.04.2021 Vers.-Nr: 50 Revision: 01.04.2021

Trade name: Transpoxy Masterbond 4.67 N Pack A

(Contd. of page 4)

several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



water:

· Viscosity:

Dynamic at 20 °C:

· Partition coefficient (n-octanol/water): Not determined.

Tightly sealed goggles

9 Physical and chemical pr	opert	ies
----------------------------	-------	-----

9 Physical and chemical properties			
Information on basic physical and c General Information	hemical properties		
· Appearance:	Fluid		
Form: Colour:			
· Odour:	According to product specification Characteristic		
· Odour: · Odour threshold:	Not determined.		
· Odour tillesiloid.			
· pH-value:	Not determined.		
· Change in condition			
Boiling point/Boiling range:	140 °C		
· Flash point:	26 °C		
· Flammability (solid, gaseous):	Not applicable.		
· Ignition temperature:	> 300 °C		
· Decomposition temperature:	Not determined.		
· Self-igniting:	Product is not selfigniting.		
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.		
· Explosion limits:			
Lower:	1,1 Vol %		
Upper:	7,0 Vol %		
· Vapour pressure:	Not determined.		
· Density at 20 °C:	1.55481 g/cm ³		
Relative density	Not determined.		
· Vapour density ·	Not determined.		
Evaporation rate	Not determined.		
· Solubility in / Miscibility with			

Not miscible or difficult to mix.

10200 mPas

(Contd. on page 6)





Vers.-Nr: 50 Printing date 01.04.2021 Revision: 01.04.2021

Trade name: Transpoxy Masterbond 4.67 N Pack A

(Contd. of page 5)

Kinematic: Not determined.

Solvent content:

VOC (EC) 235.9 a/l

Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity
- · LD/LC50 values relevant for classification:

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

		>5000 mg/kg (rat)	
	LC50/ 96 hr	1.5 mg/l (fish)	
Dermal	LD50	>2000 mg/kg (rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Serious eye damage/irritation Irritating effect.
- · Respiratory or skin sensitisation Sensitisation possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

12 Ecological information

- · Toxicity
- · Aquatic toxicity:

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

EC 50 (48 hr) 1.7 mg/l (daphnia)

EC 50 (72 hr) 9.4 mg/l (Algae)

· Persistence and degradability No further relevant information available.

(Contd. on page 7)





Printing date 01.04.2021 Vers.-Nr: 50 Revision: 01.04.2021

Trade name: Transpoxy Masterbond 4.67 N Pack A

(Contd. of page 6)

- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information	
· UN-Number · ADG, ADN, IMDG	Void
IATA	UN1263

· UN proper shipping name

· ADG, ADN, IMDG Void
· IATA Paint

- · Transport hazard class(es)
- · ADG, ADN, IMDG

· Class Void

·IATA



· Class 3 Flammable liquids.

· Label 3

· Packing group

· ADG, IMDG Void

(Contd. on page 8)



Printing date 01.04.2021 Vers.-Nr: 50 Revision: 01.04.2021

Trade name: Transpoxy Masterbond 4.67 N Pack A

		(Contd. of page 7
·IATA	III	
Environmental hazards:Marine pollutant:	No	
· Special precautions for user	Not applicable.	
 Transport in bulk according to Ann Marpol and the IBC Code 	ex II of Not applicable.	
· UN "Model Regulation":	Void	

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

mixture			
· Australian l	nventory of Chemical Substances		
14808-60-7	Quartz (SiO2)		
14807-96-6	Talc (Mg3H2(SiO3)4)		
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)		
25036-25-3	reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number avera molecular weigh > 700)	age	
1330-20-7	xylene, mixture of isomers		
13463-67-7	titanium dioxide		
100-51-6	Benzyl alcohol		
107-98-2	1-methoxy-2-propanol		
71-36-3	butan-1-ol		
2530-83-8	33-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane		
	Derivative of an organically modified hectorite		
	Xylenes		
108-65-6	2-methoxy-1-methylethyl acetate		
78-83-1	iso-butanol		
123-86-4	n-butyl acetate		
· Standard fo	or the Uniform Scheduling of Medicines and Poisons		
1330-20-7	kylene, mixture of isomers	S6	
50-00-0 f	ormaldehyde	S2, S6, S10	
111-76-2	111-76-2 2-butoxyethanol S6		
0110 1-1 -1	•	· · · · · · · · · · · · · · · · · · ·	

· GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms





GHS02 GHS07

Page 9/9



Safety data sheet according to WHS Regulations

Vers.-Nr: 50 Revision: 01.04.2021 Printing date 01.04.2021

Trade name: Transpoxy Masterbond 4.67 N Pack A

(Contd. of page 8)

· Signal word Warning

· Hazard-determining components of labelling:

xylene, mixture of isomers

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight =

reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weigh > 700)

Benzyl alcohol

· Hazard statements

Flammable liquid and vapour.

Causes skin irritation. Causes

serious eye irritation.

May cause an allergic skin reaction.

Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical/ventilating/lighting/equipment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

· * Data compared to the previous version altered.