



# T12 Gunwash

Code: THT120000

## Description

- Solvent for cleaning of spray guns and other application equipment immediately after use

## Properties

- Particularly effective for air-dry enamel coatings

## Typical Applications

- Cleaning of spray guns, pressure pots, spray lines, paint cans, etc.
- Paint residue must still be wet; best results when applied shortly after equipment use
- Best suited to air-dry alkyds such as Zip Dry Enamel, Rapid Enamel, Purlenamel, etc.

## General Data

- Recycled blend of hydrocarbon and chemical solvents

## Specifications (at 25°C and 50% relative humidity)

- Appearance.....Low viscosity, clear, water-white liquid
- Specific Gravity.....0.80
- Boiling Range..... 47 - 197°C

## Mixing recommendation

- Apply liberal amounts of T12 and flush through equipment or scrub with stiff bristle brush

## Safety precautions

- **Refer to the relevant Safety Data Sheet**
- Contents are flammable – keep away from all ignition sources
- Avoid contact with skin and eyes – when mixing, wear gloves and goggles
- When spraying, ensure adequate ventilation and wear appropriate protective clothing and equipment

**Packaging Group II**      **UN No. 1263**

**Pack sizes**      4 litre, 20 litre, 200 litre

Authorised:      A. De Mello, Sales Manager

February 2023

These technical data and recommendations are based on tests and information believed to be accurate at the time of printing. They should not be construed as containing any warranty, either expressed or implied. Users should conduct their own tests to determine final suitability of this product.



**Wagon Paints**

**5 Stephenson Road, Bayswater North, Victoria 3153 Australia**  
**Phone: 61 3 97291344 Fax: 61 3 97202179 Email: sales@wagonpaints.com.au**