



T29 Prepwash

Code: THT290000

Description

- Solvent blend for removing wax, grease and other contaminants from bare metal

Properties

- Good solvency for most contaminants
- Leaves surface in best condition for painting

Typical Applications

- Cleaning of steel, aluminium, galvanised iron, etc. prior to painting

General Data

- Specially formulated blend of solvents

Specifications (at 25°C and 50% relative humidity)

- Appearance.....Low viscosity, clear, water-white liquid
- Specific Gravity.....0.73
- Boiling Range..... 47 - 197°C

Cleaning recommendation

- Apply liberal amount of T29 to surface to be cleaned
- Always use clean T29 Prepwash Remover and clean rags
- Remove by wiping in one direction

Safety precautions

- **Refer to the relevant Material Safety Data Sheet**
- Contents are flammable – keep away from all ignition sources
- Avoid contact with skin and eyes – when mixing, wear gloves and goggles
- When spraying, ensure adequate ventilation and wear appropriate protective clothing and equipment

Packaging Group II **UN No. 1263**

Pack sizes 4 litre, 20 litre

Authorised: A. De Mello, Sales Manager

February 2023

These technical data and recommendations are based on tests and information believed to be accurate at the time of printing. They should not be construed as containing any warranty, either expressed or implied. Users should conduct their own tests to determine final suitability of this product.



Wagon Paints

5 Stephenson Road, Bayswater North, Victoria 3153 Australia
Phone: 61 3 97291344 Fax: 61 3 97202179 Email: sales@wagonpaints.com.au