

T8 Thinner

Code: THT80000

Description

Thinner for reducing specific coatings to application viscosity

Properties

- Good combination of initial hold-up and final flow-out
- Excellent solvency

Typical Applications

Thinning of Colgal and Thermosil HR for spray application

General Data

Specially formulated blend of hydrocarbon solvents

Specifications (at 25°C and 50% relative humidity)

- Appearance.....Low viscosity, clear, water-white liquid
- Boiling Range.......106 119°C

Mixing recommendation

Refer to individual Product Data Sheets for the products listed above

Safety precautions

- Refer to the relevant Material Safety Data Sheet
- Contents are flammable keep away from all ignition sources
- Avoid contact with skin and eyes when mixing, wear gloves and goggles
- When spraying, ensure adequate ventilation and wear appropriate protective clothing and equipment

Packaging Group II UN No. 1193

Pack sizes 1 litre, 4 litre, 20 litre

Authorised: A. De Mello, Sales Manager February 2023

These technical data and recommendations are based on tests and information believed to be accurate at the time of printing. They should not be construed as containing any warranty, either expressed or implied. Users should conduct



Wagon Paints

their own tests to determine final suitability of this product.

5 Stephenson Road, Bayswater North, Victoria 3153 Australia Phone: 61 3 97291344 Fax: 61 3 97202179 Email: sales@wagonpaints.com.au