



T9 Universal Thinner

Code: THT90000

Description

- Multi-purpose thinner for reducing various coatings to application viscosity

Properties

- Good combination of initial hold-up and final flow-out
- Excellent solvency

Typical Applications

- Thinning of NC lacquers, Air-dry Enamels and Baking Enamels for spray application
- May be used with some Acrylic lacquers (test with sample before using generally)

General Data

- Specially formulated blend of hydrocarbon and chemical solvents

Specifications (at 25°C and 50% relative humidity)

- Appearance..... Low viscosity, clear, water-white liquid
- Specific Gravity.....0.80
- Boiling Range..... 80 - 130°C

Mixing recommendation

- Refer to individual Product Data Sheets for the products listed above

Safety precautions

- **Refer to the relevant Material Safety Data Sheet**
- Contents are flammable – keep away from all ignition sources
- Avoid contact with skin and eyes – when mixing, wear gloves and goggles
- When spraying, ensure adequate ventilation and wear appropriate protective clothing and equipment

Packaging Group II **UN No. 1263**

Pack sizes 1 litre, 4 litre, 20 litre, 200 litre

Authorised: A. De Mello, Sales Manager

February 2023

These technical data and recommendations are based on tests and information believed to be accurate at the time of printing. They should not be construed as containing any warranty, either expressed or implied. Users should conduct their own tests to determine final suitability of this product.



Wagon Paints

5 Stephenson Road, Bayswater North, Victoria 3153 Australia
Phone: 61 3 97291344 Fax: 61 3 97202179 Email: sales@wagonpaints.com.au