

Page 1/9

Safety data sheet according to WHS Regulations

Vers.-Nr: 57

Revision: 23.05.2023

Hazardous according to criteria of Australian Safety and Compensation Council

1 Identification

- · Product identifier
- · Trade name: Transozinc Silicate 1.52 pack A
- · Article number: 152a
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- Application of the substance/preparation: Hardening agent/ Curing agent Paint
- · Details of the supplier of the safety data sheet
- Manufacturer/supplier: Transocean Coatings Wagon Paints Australia Pty Ltd ABN: 76 412 791 772 Street address: 5 Stephenson Road, Bayswater North VIC, 3153 Australia Phone: +613 9729-1344 Fax: +613 9720 2719
- Emergency telephone number:
- Medical Emergencies: 24 Hours
- Poisons Information Centre (Australia): 131 126

2 Hazard Identification

· Classification of the substance or mixture

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS). • Hazard pictograms



- · Signal word Danger
- Hazard-determining components of labelling: tetraethyl silicate
- Hazard statements
 Highly flammable liquid and vapour.
 Causes serious eye irritation.
 May cause drowsiness or dizziness.
- **Precautionary statements** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



Page 2/9

Safety data sheet according to WHS Regulations

Vers.-Nr: 57

Revision: 23.05.2023

Trade name: Transozinc Silicate 1.52 pack A

(Contd. of page 1)

Use explosion-proof electrical/ventilating/lighting/equipment. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations. • Other hazards

- · Other Hazarus
- \cdot Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition and information on ingredients

· Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
67-63-0	propan-2-ol		25-50%	
	Flam. Liq. 2, H225;	Eye Irrit. 2, H319; STOT SE 3, H336		
78-10-4	tetraethyl silicate		2,5-10%	
	Flam. Liq. 3, H226; H335	Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3,		
64-17-5	ethanol		≤ 2,5%	
	Flam. Liq. 2, H225			

• Additional information: For the wording of the listed risk phrases refer to section 16.

4 First Aid Measures

- · Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture
- No further relevant information available.

(Contd. on page 3)



Safety data sheet according to WHS Regulations

Vers.-Nr: 57

Revision: 23.05.2023

Trade name: Transozinc Silicate 1.52 pack A

· Advice for firefighters

· Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:
 Dilute with plenty of water.
 Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
 Store in each dry conditions in well contained recented

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· Control parameters

••••••••••••••••••	
 Ingredients with limit valu 	es that require monitoring at the workplace:
67-63-0 propan-2-ol	
NES Short-term value: 123	0 mg/m³, 500 ppm
NES Short-term value: 123 Long-term value: 983	mg/m³, 400 ppm
78-10-4 tetraethyl silicate	
NES Long-term value: 85 n	ng/m³, 10 ppm
	(Contd. on page 4)
	AU

Page 3/9



Safety data sheet according to WHS Regulations

Vers.-Nr: 57

Revision: 23.05.2023

Trade name: Transozinc Silicate 1.52 pack A

	(Contd. of page 2)
64-17	7-5 ethanol
NES	Long-term value: 1880 mg/m ³ , 1000 ppm

• Additional information: The lists valid during the making were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Information on basic physic	al and chemical properties	
· General Information		
· Appearance:		
Form:	Fluid	
Colour:	According to product specification	
· Odour:	Characteristic	
· Odour threshold:	Not determined.	



Page 5/9

Safety data sheet according to WHS Regulations

Vers.-Nr: 57

Revision: 23.05.2023

Trade name: Transozinc Silicate 1.52 pack A

	(Contd. of page 2
· pH-value:	Not determined.
 Change in condition Boiling point/Boiling range: 	82 °C
· Flash point:	13 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	425 °C
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits: Lower: Upper:	2.0 Vol % 12.0 Vol %
· Vapour pressure at 20 °C:	43 hPa
 Density at 20 °C: Relative density Vapour density Evaporation rate 	0.928 g/cm ³ Not determined. Not determined. Not determined.
 Solubility in / Miscibility with water: 	Fully miscible.
· Partition coefficient (n-octanol/wat	er): Not determined.
 Viscosity: Dynamic at 20 °C: Kinematic: 	2000 mPas Not determined.
 Solvent content: Water: VOC (EC) Other information 	6.3 % 401.0 g/l No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 6)



Safety data sheet according to WHS Regulations

Vers.-Nr: 57

Revision: 23.05.2023

Trade name: Transozinc Silicate 1.52 pack A

(Contd. of page 2)

Page 6/9

11 Toxicological information

· Information on toxicological effects

- · Acute toxicity
- · Primary irritant effect:
- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation Irritating effect.

· Respiratory or skin sensitisation No sensitising effects known.

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

4 Transport information	
· UN-Number · ADG, IMDG, IATA	UN1263
 UN proper shipping name ADG 	1263 PAINT, special provision 640H
	(Contd. on page

AU



Page 7/9

Safety data sheet according to WHS Regulations

Vers.-Nr: 57

Revision: 23.05.2023

Trade name: Transozinc Silicate 1.52 pack A

	(Contd. of page 2
· IMDG · IATA	PAINT Paint
· Transport hazard class(es)	
· ADG, IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· Packing group · ADG, IMDG, IATA	III
 Environmental hazards: Marine pollutant: 	No
· Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler): · EMS Number:	-
· Stowage Category	F-E, <u>S-E</u> A
Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
 ADG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
 Transport category Tunnel restriction code 	3 E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, SPECIAL PROVISION 640H, 3, III

15 Regulatory information

 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Chemical Substances

68412-37-3 Partially hydrolysed ethyl silicate

67-63-0 propan-2-ol

78-10-4 tetraethyl silicate

(Contd. on page 8)

AU



Page 8/9

Safety data sheet according to WHS Regulations

Vers.-Nr: 57

Revision: 23.05.2023

Trade name: Transozinc Silicate 1.52 pack A

 64-17-5
 ethanol

 7732-18-5
 water, distilled, conductivity or of similar purity

 • Standard for the Uniform Scheduling of Medicines and Poisons

None of the ingredients is listed.

· GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms



- · Signal word Danger
- Hazard-determining components of labelling: tetraethyl silicate
- · Hazard statements

Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical/ventilating/lighting/equipment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Abbreviations and acronyms:
 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations
 Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the
 International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 (Contd. on page 9)



Page 9/9

Safety data sheet according to WHS Regulations

Vers.-Nr: 57

Revision: 23.05.2023

Trade name: Transozinc Silicate 1.52 pack A

(Contd. of page 2)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids, Hazard Category 2 Flam. Liq. 3: Flammable liquids, Hazard Category 3 Acute Tox. 4: Acute toxicity, Hazard Category 4 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 • * Data compared to the previous version altered.