

# Safety Data Sheet according to WHS Regulations

Vers.-Nr: 53

Revision: 23.05.2023

Hazardous according to criteria of Australian Safety and Compensation Council.

## 1 Identification

- **Product identifier**
- **Trade name:** Transozinc Silicate 1.52 PACK B
- **Article number:** 152b
- **Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance/preparation:** Paint
- **Details of the supplier of the safety data sheet**
- **Manufacturer/supplier:**  
Transocean Coatings  
Wagon Paints Australia Pty Ltd  
ABN: 76 412 791 772  
Street address: 5 Stephenson Road, Bayswater North  
VIC, 3153 Australia  
Phone: +613 9729-1344  
Fax: +613 9720 2719
- **Emergency telephone number:**
- Medical Emergencies: 24 Hours
- Poisons Information Centre (Australia): 131 126

## 2 Hazard(s) Identification

- **Classification of the substance or mixture**  
Flam. Liq. 3 H226 Flammable liquid and vapour.
- **Label elements**
- **GHS label elements**  
The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**



GHS02

- **Signal word** Warning
- **Hazard statements**  
H226 Flammable liquid and vapour.
- **Precautionary statements**  
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting equipment.  
P242 Use only non-sparking tools. Take precautionary measures  
P243 against static discharge.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.  
Rinse skin with water/shower.

(Contd. on page 2)

## Safety Data Sheet according to WHS Regulations

Vers.-Nr: 53

Revision: 23.05.2023

**Trade name: Transozinc Silicate 1.52 PACKB**

(Contd. of page 1)

P403+P235 Store in a well-ventilated place. Keep cool.  
P501 Dispose of contents/container in accordance with local/regional/national/  
international regulations.

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition and Information on Ingredients

- **Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

107-98-2	1-methoxy-2-propanol ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	2.5-10%
1330-20-7	xylene, mixture of isomers ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H335	≥2.5-<10%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### 4 First Aid Measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire Fighting Measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

### 6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

## Safety Data Sheet according to WHS Regulations

Vers.-Nr: 53

Revision: 23.05.2023

**Trade name: Transozinc Silicate 1.52 PACK B**

(Contd. of page 2)

- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and Storage

- **Handling:**
- **Precautions for safe handling**  
Use only in well ventilated areas.  
Store in cool, dry place in tightly closed receptacles.  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**107-98-2 1-methoxy-2-propanol**

WES	Short-term value: 553 mg/m <sup>3</sup> , 150 ppm
	Long-term value: 369 mg/m <sup>3</sup> , 100 ppm

**1330-20-7 xylene, mixture of isomers**

WES	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm
	Long-term value: 350 mg/m <sup>3</sup> , 80 ppm

· **DNELs**

**7440-66-6 zinc powder -zinc dust (stabilized)**

Inhalative	long term DNEL	5 mg/m <sup>3</sup> (Workers)
------------	----------------	-------------------------------

**107-98-2 1-methoxy-2-propanol**

Oral	long term DNEL	3.3 mg/kg/d (General Population)
Dermal	long term DNEL	18.1 mg/kg/d (General Population)
		50.6 mg/kg/d (Workers)
Inhalative	long term DNEL	43.9 mg/m <sup>3</sup> (General Population)
		369 mg/m <sup>3</sup> (Workers)

(Contd. on page 4)

## Safety Data Sheet according to WHS Regulations

Vers.-Nr: 53

Revision: 23.05.2023

**Trade name: Transozinc Silicate 1.52 PACK B**

(Contd. of page 3)

	Acute DNEL	553.5 mg/m <sup>3</sup> (Workers)
<b>1330-20-7 xylene, mixture of isomers</b>		
Dermal	long term DNEL	108 mg/kg/d (General Population) 180 mg/kg/d (Workers)
Inhalative	long term DNEL	14.8 mg/m <sup>3</sup> (General Population) 77 mg/m <sup>3</sup> (Workers)
· <b>PNECs</b>		
<b>107-98-2 1-methoxy-2-propanol</b>		
PNEC STP		100 mg/l (water treatment plant)
PNEC aqua		10000 ug/l (freshwater)
PNEC sediment		41.6 mg/kg (freshwater) 4.17 mg/kg (marine water)
PNEC soil		2.47 mg/kg (Soil)
<b>1330-20-7 xylene, mixture of isomers</b>		
PNEC STP		6.58 mg/l (water treatment plant)
PNEC aqua		327 ug/l (freshwater) 327 ug/l (marine water)
PNEC sediment		12.46 mg/kg (freshwater) 12.46 mg/kg (marine water)
PNEC soil		2.31 mg/kg (Soil)

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:** Wash hands before breaks and at the end of work.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

## Safety Data Sheet according to WHS Regulations

Vers.-Nr: 53

Revision: 23.05.2023

**Trade name: Transozinc Silicate 1.52 PACK B**

(Contd. of page 4)

· **Eye protection:**



Tightly sealed goggles

### 9 Physical and Chemical Properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

**Form:** Fluid  
    **Colour:** According to product specification

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

**Melting point/freezing point:** Undetermined.  
    **Initial boiling point and boiling range:** 82 °C

· **Flash point:** 25 °C

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 287 °C

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

**Lower:** Not determined.  
    **Upper:** Not determined.

· **Vapour pressure:** Not determined.

· **Density at 20 °C:** 3.214 g/cm<sup>3</sup>

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient: n-octanol/water:** Not determined.

· **Viscosity:**

**Dynamic at 20 °C:** 2000 mPas  
    **Kinematic:** Not determined.

· **Solvent content:**

**VOC (EC)** 478.9 g/l

(Contd. on page 6)

## Safety Data Sheet according to WHS Regulations

Vers.-Nr: 53

Revision: 23.05.2023

**Trade name: Transozinc Silicate 1.52 PACK B**

(Contd. of page 5)

· **Other information** No further relevant information available.

### 10 Stability and Reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological Information

- **Information on toxicological effects**
- **Acute toxicity**

· **LD/LC50 values relevant for classification:**

**7440-66-6 zinc powder -zinc dust (stabilized)**

Oral	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4 h (dynamic)	5.4 mg/l (rat)

**107-98-2 1-methoxy-2-propanol**

Oral	LD50	4016 mg/kg (rat)
	LC50/ 96 hr	6812 mg/l (fish)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	6 mg/l (rat)

**1330-20-7 xylene, mixture of isomers**

Oral	LD50	>2000 mg/kg (rat)
	LC50/ 96 hr (static)	2.6 mg/l (Rainbow trout ( <i>Oncorhynchus mykiss</i> )) (OESO 203 or equivalent)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>20 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.

### 12 Ecological Information

- **Toxicity**

· **Aquatic toxicity:**

**107-98-2 1-methoxy-2-propanol**

EC 50 (48 hr)	23300 mg/l (daphnia)
---------------	----------------------

(Contd. on page 7)

## Safety Data Sheet according to WHS Regulations

Vers.-Nr: 53

Revision: 23.05.2023

**Trade name: Transozinc Silicate 1.52 PACK B**

(Contd. of page 6)

**1330-20-7 xylene, mixture of isomers**

EC 50 (48 hr) 1-10 mg/l (daphnia)



EC 50 (72 hr) 1-10 mg/l (Algae)

- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Very toxic for fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
Very toxic for aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- **UN-Number**
- **ADG, IMDG, IATA** UN1263
- **UN proper shipping name**
- **ADG** 1263 PAINT, ENVIRONMENTALLY HAZARDOUS
- **IMDG** PAINT (zinc powder -zinc dust (stabilized)),
- **IATA** MARINE POLLUTANT
- **IATA** PAINT
- **Transport hazard class(es)**
- **ADG, IMDG**
- 

- **Class** 3 Flammable liquids.

(Contd. on page 8)


## Safety Data Sheet according to WHS Regulations

Vers.-Nr: 53

Revision: 23.05.2023

**Trade name: Transozinc Silicate 1.52 PACK B**

(Contd. of page 7)

<b>· Label</b>	3
<b>· IATA</b>	
	
<b>· Class</b>	3 Flammable liquids.
<b>· Label</b>	3
<b>· Packing group</b>	
<b>· ADG, IMDG, IATA</b>	III
<b>· Environmental hazards:</b>	
<b>· Marine pollutant:</b>	Yes Symbol (fish and tree)
<b>· Special marking (ADG):</b>	Symbol (fish and tree)
<b>· Special precautions for user</b>	Warning: Flammable liquids.
<b>· Hazard identification number (Kemler code):</b>	30
<b>· EMS Number:</b>	F-E, <u>S-E</u>
<b>· Stowage Category</b>	A
<b>· Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
<b>· Transport/Additional information:</b>	
<b>· ADG</b>	
<b>· Limited quantities (LQ)</b>	5L
<b>· Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<b>· Transport category</b>	3
<b>· Tunnel restriction code</b>	D/E
<b>· IMDG</b>	
<b>· Limited quantities (LQ)</b>	5L
<b>· Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<b>· UN "Model Regulation":</b>	UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

### 15 Regulatory information

**· Safety, health and environmental regulations/legislation specific for the substance or mixture**

**· Australian Inventory of Industrial Chemicals**

107-98-2	1-methoxy-2-propanol
----------	----------------------

(Contd. on page 9)



## Safety Data Sheet according to WHS Regulations

Vers.-Nr: 53

Revision: 23.05.2023

**Trade name: Transozinc Silicate 1.52 PACK B**

(Contd. of page 8)

1330-20-7	xylene, mixture of isomers	
68648-78-2	Mowital	
	Derivative of an organically modified hectorite	
14808-60-7	Quartz (SiO <sub>2</sub> )	
<ul style="list-style-type: none"> <li>• <b>Standard for the Uniform Scheduling of Medicines and Poisons</b></li> </ul>		
1330-20-7	xylene, mixture of isomers	S6
<ul style="list-style-type: none"> <li>• <b>Australia: Priority Existing Chemicals</b></li> </ul>		
None of the ingredients is listed.		

- **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

- **Hazard pictograms**



GHS02

- **Signal word** Warning

- **Hazard statements**

H226 Flammable liquid and vapour.

- **Precautionary statements**

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
 P233 Keep container tightly closed.  
 P240 Ground/bond container and receiving equipment.  
 P241 Use explosion-proof electrical/ventilating/lighting equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P403+P235 Store in a well-ventilated place. Keep cool.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Directive 2012/18/EU**

• **Named dangerous substances - ANNEX I** None of the ingredients is listed.

- **Seveso category**

E1 Hazardous to the Aquatic Environment  
 P5c FLAMMABLE LIQUIDS

• **Qualifying quantity (tonnes) for the application of lower-tier requirements** 100 t

• **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t

• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Contact:**

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 10)

## Safety Data Sheet according to WHS Regulations

Vers.-Nr: 53

Revision: 23.05.2023

**Trade name: Transozinc Silicate 1.52 PACK B**

(Contd. of page 9)

ICAO: International Civil Aviation Organisation  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
VOC: Volatile Organic Compounds (USA, EU)  
DNEL: Derived No-Effect Level (REACH)  
PNEC: Predicted No-Effect Concentration (REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Liq. 3: Flammable liquids – Category 3  
Acute Tox. 4: Acute toxicity - dermal – Category 4  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

• **\* Data compared to the previous version altered.**

AU