

# Safety data sheet according to WHS Regulations

Vers.-Nr: 48



Revision: 23.05.2023

Hazardous according to criteria of Australian Safety and Compensation Council

## 1 Identification

- **Product identifier**
- **Trade name:** Transpoxy ZP primer 1.61 pack A
- **Article number:** 161a-2
- **Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance/preparation:**  
Epoxy coating  
Paint
- **Details of the supplier of the safety data sheet**
- **Manufacturer/supplier:**  
Transocean Coatings  
Wagon Paints Australia Pty Ltd  
ABN: 76 412 791 772  
Street address: 5 Stephenson Road, Bayswater North  
VIC, 3153 Australia  
Phone: +613 9729-1344  
Fax: +613 9720 2719
- **Emergency telephone number:** Medical Emergencies: 24 Hours
- **Poisons Information Centre (Australia):** 131 126

## 2 Hazard Identification

- **Classification of the substance or mixture**  
Flam. Liq. 3 H226 Flammable liquid and vapour.  
Skin Irrit. 2 H315 Causes skin irritation.  
Eye Irrit. 2 H319 Causes serious eye irritation.  
Skin Sens. 1 H317 May cause an allergic skin reaction.
- **Label elements**
- **GHS label elements**  
The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**  
  
GHS02 GHS07
- **Signal word** Warning
- **Hazard-determining components of labelling:**  
xylene, mixture of isomers  
reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight > 700)
- **Hazard statements**  
Flammable liquid and vapour.  
Causes skin irritation.

(Contd. on page 2)

## Safety data sheet according to WHS Regulations

Vers.-Nr: 48

Revision: 23.05.2023

**Trade name: Transpoxy ZP primer 1.61 pack A**

(Contd. of page 1)

Causes serious eye irritation.

May cause an allergic skin reaction.

· **Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### 3 Composition and information on ingredients

· **Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

1330-20-7	xylene, mixture of isomers Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	10-25%
25036-25-3	reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weigh > 700) Skin Sens. 1, H317	10-25%
78-83-1	iso-butanol Flam. Liq. 3, H226; Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335-H336	≤ 2,5%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

### 4 First Aid Measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

AU

(Contd. on page 3)

## Safety data sheet according to WHS Regulations

Vers.-Nr: 48

Revision: 23.05.2023

Trade name: Transpoxy ZP primer 1.61 pack A

(Contd. of page 2)

### 5 Fire Fighting Measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**  
No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

#### Ingredients with limit values that require monitoring at the workplace:

##### 1330-20-7 xylene, mixture of isomers

NES	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 350 mg/m <sup>3</sup> , 80 ppm
-----	--

(Contd. on page 4)

## Safety data sheet

### according to WHS Regulations

Vers.-Nr: 48

Revision: 23.05.2023

Trade name: Transpoxy ZP primer 1.61 pack A

(Contd. of page 2)

<b>78-83-1 iso-butanol</b>		
NES	Long-term value: 152 mg/m <sup>3</sup> , 50 ppm	
· <b>DNELs</b>		
<b>1330-20-7 xylene, mixture of isomers</b>		
Dermal	long term DNEL	108 mg/kg/d (General Population) 180 mg/kg/d (Workers)
Inhalative	long term DNEL	14.8 mg/m <sup>3</sup> (General Population) 77 mg/m <sup>3</sup> (Workers)
<b>7779-90-0 trizinc bis(orthophosphate)</b>		
Inhalative	long term DNEL	5 mg/m <sup>3</sup> (Workers)
<b>1314-13-2 zinc oxide</b>		
Oral	long term DNEL	0.83 mg/kg/d (General Population)
Dermal	long term DNEL	83 mg/kg/d (General Population)
Inhalative	long term DNEL	2.5 mg/m <sup>3</sup> (General Population) 5 mg/m <sup>3</sup> (Workers)
· <b>PNECs</b>		
<b>1330-20-7 xylene, mixture of isomers</b>		
PNEC STP	6.58 mg/l (water treatment plant)	
PNEC aqua	327 ug/l (freshwater) 327 ug/l (marine water)	
PNEC sediment	12.46 mg/kg (freshwater) 12.46 mg/kg (marine water)	
PNEC soil	2.31 mg/kg (Soil)	
<b>7779-90-0 trizinc bis(orthophosphate)</b>		
PNEC STP	0.052 mg/l (water treatment plant)	
PNEC aqua	20.6 ug/l (freshwater) 6.1 ug/l (marine water)	
PNEC sediment	235.6 mg/kg (freshwater) 113 mg/kg (marine water)	
PNEC soil	106.8 mg/kg (Soil)	
<b>1314-13-2 zinc oxide</b>		
PNEC STP	0.52 mg/l (water treatment plant)	
PNEC aqua	20.6 ug/l (freshwater) 6.1 ug/l (marine water)	
PNEC sediment	117.8 mg/kg (freshwater)	

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing  
 Wash hands before breaks and at the end of work.  
 Avoid contact with the eyes and skin.

(Contd. on page 5)

AU

## Safety data sheet according to WHS Regulations

Vers.-Nr: 48

Revision: 23.05.2023

**Trade name: Transpoxy ZP primer 1.61 pack A**

(Contd. of page 2)

- **Respiratory protection:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

### 9 Physical and chemical properties

<ul style="list-style-type: none"> <li>· <b>Information on basic physical and chemical properties</b></li> <li>· <b>General Information</b></li> <li>· <b>Appearance:</b></li> </ul>	
Form:	Fluid
Colour:	According to product specification
· <b>Odour:</b>	Characteristic
· <b>Odour threshold:</b>	Not determined.
· <b>pH-value:</b>	Not determined.
<ul style="list-style-type: none"> <li>· <b>Change in condition</b></li> <li>  <b>Boiling point/Boiling range:</b></li> </ul>	
	137 °C
· <b>Flash point:</b>	25 °C
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Ignition temperature:</b>	500 °C
· <b>Decomposition temperature:</b>	Not determined.
· <b>Self-igniting:</b>	Product is not selfigniting.

(Contd. on page 6)

## Safety data sheet according to WHS Regulations

Vers.-Nr: 48

Revision: 23.05.2023

Trade name: Transpoxy ZP primer 1.61 pack A

(Contd. of page 2)

· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	1.1 Vol %
<b>Upper:</b>	7.0 Vol %
· <b>Vapour pressure at 20 °C:</b>	6.7 hPa
· <b>Density at 20 °C:</b>	1.84031 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic at 20 °C:</b>	2500 mPas
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>VOC (EC)</b>	415.2 g/l
· <b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

#### LD/LC50 values relevant for classification:

#### 1330-20-7 xylene, mixture of isomers

Oral	LD50	>2000 mg/kg (rat)
	LC50/ 96 hr (static)	2.6 mg/l (Rainbow trout ( <i>Oncorhynchus mykiss</i> )) (OESO 203 or equivalent)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>20 mg/l (rat)

(Contd. on page 7)

AU

## Safety data sheet

### according to WHS Regulations

Vers.-Nr: 48

Revision: 23.05.2023

Trade name: Transpoxy ZP primer 1.61 pack A

(Contd. of page 2)

<b>7779-90-0 trizinc bis(orthophosphate)</b>		
Oral	LD50	>5000 mg/kg (rat)
	LC50/ 96 hr	0.33 - 6.06 mg/l (Rainbow trout (Oncorhynchus mykiss))
Dermal	LD50	552 mg/kg (mouse)
Inhalative	LC50/4 h	>5.7 mg/l (rat)
<b>1314-13-2 zinc oxide</b>		
Oral	LD50	7950 mg/kg (rat)
Inhalative	LC50/4 h	5.7 mg/l (rat)

- **Primary irritant effect:**

- **Skin corrosion/irritation** Irritant to skin and mucous membranes.

- **Serious eye damage/irritation** Irritating effect.

- **Respiratory or skin sensitisation** Sensitisation possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

## \* 12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

### **1330-20-7 xylene, mixture of isomers**

EC 50 (48 hr)	1-10 mg/l (daphnia)
EC 50 (72 hr)	1-10 mg/l (Algae)

### **7779-90-0 trizinc bis(orthophosphate)**

EC 50 (48 hr)	0.96 mg/l (daphnia)
EC 50 (72 hr)	0.32 mg/l (Algae)

### **1314-13-2 zinc oxide**

EC 50 (48 hr)	0.67 mg/l (daphnia)
EC 50 (72 hr)	0.21 mg/l (Algae)

## Safety data sheet according to WHS Regulations

Vers.-Nr: 48

Revision: 23.05.2023

Trade name: Transpoxy ZP primer 1.61 pack A




(Contd. of page 2)

- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

<ul style="list-style-type: none"> <li>· UN-Number</li> <li>· ADG, IMDG, IATA</li> </ul>	UN1263
<ul style="list-style-type: none"> <li>· UN proper shipping name</li> <li>· ADG</li> <li>· IMDG</li> <li>· IATA</li> </ul>	1263 PAINT, ENVIRONMENTALLY HAZARDOUS, special provision 640E PAINT (trizinc bis(orthophosphate), zinc oxide), MARINE POLLUTANT Paint
<ul style="list-style-type: none"> <li>· Transport hazard class(es)</li> <li>· ADG, IATA</li> </ul> 	3 Flammable liquids.
<ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> </ul>	3
<ul style="list-style-type: none"> <li>· IMDG</li> </ul>  	3 Flammable liquids.
<ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> </ul>	3
<ul style="list-style-type: none"> <li>· Packing group</li> <li>· ADG, IMDG, IATA</li> </ul>	III
<ul style="list-style-type: none"> <li>· Environmental hazards:</li> <li>· Marine pollutant:</li> </ul>	Product contains environmentally hazardous substances: Yes Symbol (fish and tree)
<ul style="list-style-type: none"> <li>· Special precautions for user</li> <li>· Danger code (Kemler):</li> </ul>	Warning: Flammable liquids. 30

(Contd. on page 9)

AU



## Safety data sheet according to WHS Regulations

Vers.-Nr: 48

Revision: 23.05.2023

Trade name: Transpoxy ZP primer 1.61 pack A

(Contd. of page 2)

· EMS Number:	F-E, <u>S-E</u>
· Stowage Category	A
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, SPECIAL PROVISION 640E, 3, III, ENVIRONMENTALLY HAZARDOUS

### 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Chemical Substances

1330-20-7	xylene, mixture of isomers
7779-90-0	trizinc bis(orthophosphate)
25036-25-3	reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weigh > 700)
14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )
1309-37-1	Red iron oxide
1317-61-9	Pigment black 11
1314-13-2	zinc oxide
78-83-1	iso-butanol
20344-49-4	Yellow iron oxide
	Derivative of an organically modified hectorite
64742-94-5	Solvent naphtha (petroleum), heavy arom.
108-65-6	2-methoxy-1-methylethyl acetate
57-55-6	propane-1,2-diol
78-92-2	butanol

· Standard for the Uniform Scheduling of Medicines and Poisons

1330-20-7	xylene, mixture of isomers	S6
-----------	----------------------------	----

· GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

(Contd. on page 10)

AU

## Safety data sheet according to WHS Regulations

Vers.-Nr: 48

Revision: 23.05.2023

Trade name: Transpoxy ZP primer 1.61 pack A

(Contd. of page 9)

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Warning

· **Hazard-determining components of labelling:**

xylene, mixture of isomers

reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight > 700)

· **Hazard statements**

Flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

· **Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category**

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

(Contd. on page 11)

## Safety data sheet according to WHS Regulations

Vers.-Nr: 48

Revision: 23.05.2023

**Trade name: Transpoxy ZP primer 1.61 pack A**

(Contd. of page 10)

LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Liq. 3: Flammable liquids, Hazard Category 3  
Acute Tox. 4: Acute toxicity, Hazard Category 4  
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2  
Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1  
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2  
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1  
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

- **\* Data compared to the previous version altered.**

AU