



Vers.-Nr: 53 Revision: 23.05.2023

Hazardous according to criteria of Australian Safety and Compensation Council

1 Identification

· Product identifier

· Trade name: Transpoxy ZP primer 1.61 pack B

· Article number: 161b

· Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance/preparation:

Epoxy curing agent

Paint

· Details of the supplier of the safety data sheet

· Manufacturer/supplier:

Transocean Coatings

Wagon Paints Australia Pty Ltd

ABN: 76 412 791 772

Street address: 5 Stephenson Road, Bayswater North

VIC, 3153 Australia Phone: +613 9729-1344 Fax: +613 9720 2719

· Emergency telephone number: Medical Emergencies: 24 Hours

· Poisons Information Centre (Australia): 131 126

2 Hazard Identification

· Classification of the substance or mixture

Flam. Lig. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

- · Label elements
- · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms





GHS02 GHS05

- · Signal word Danger
- · Hazard-determining components of labelling:

reaction product based on fatty acids and polyethyleneamine xylene, mixture of isomers

butan-1-ol

Hazard statements

Flammable liquid and vapour.

Causes skin irritation.

Causes serious eye damage.





Vers.-Nr: 53 Revision: 23.05.2023

Trade name: Transpoxy ZP primer 1.61 pack B

(Contd. of page 1)

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical/ventilating/lighting/equipment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

3 Composition and information on ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:					
68410-23-1	reaction product based on fatty acids and polyethyleneamine				
	Eye Dam. 1, H318				
1330-20-7	xylene, mixture of isomers	25-50%			
	Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315				
	butan-1-ol	2,5-10%			
	Flam. Liq. 3, H226; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336				
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	2,5-10%			
	Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319				

[·] Additional information: For the wording of the listed risk phrases refer to section 16.

4 First Aid Measures

- Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)





Vers.-Nr: 53 Revision: 23.05.2023

Trade name: Transpoxy ZP primer 1.61 pack B

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture
 No further relevant information available.
- · Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)





Vers.-Nr: 53 Revision: 23.05.2023

Trade name: Transpoxy ZP primer 1.61 pack B

(Contd. of page 3)

· Control parameters

· Ingre	· Ingredients with limit values that require monitoring at the workplace:						
1330	1330-20-7 xylene, mixture of isomers						
NES		nort-term value: 655 mg/m³, 150 ppm					
	Long-term value: 350 mg/m³, 80 ppm						
71-36	71-36-3 butan-1-ol						
NES	Peak limitation: 152 mg/m³, 50 ppm						
	Sk						
· DNE	· DNELs						
1330	1330-20-7 xylene, mixture of isomers						
Derm	Dermal I		erm DNEL	108 mg/kg/d (General Population)			
				180 mg/kg/d (Workers)			
Inhal	ative	long term DNEL		14.8 mg/m3 (General Population)			
				77 mg/m3 (Workers)			
· PNE	Cs						
1330	1330-20-7 xylene, mixture of isomers						
PNE	PNEC STP		6.58 mg/l (water treatment plant)				
PNE	PNEC aqua		327 ug/l (freshwater)				
			327 ug/l (marine water)				
PNE	PNEC sedimen		12.46 mg/kg (freshwater)				
			12.46 mg/kg (marine water)				
PNE	PNEC soil 2.31 mg/kg			g (Soil)			

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)





Vers.-Nr: 53 Revision: 23.05.2023

Trade name: Transpoxy ZP primer 1.61 pack B

· Material of gloves

(Contd. of page 4)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

9 Physical and chemical prop	perties			
· Information on basic physical and chemical properties				
· General Information	• •			
· Appearance:				
Form:	Fluid			
Colour:	According to product specification			
· Odour:	Characteristic			
· Odour threshold:	Not determined.			
· pH-value:	Not determined.			
· Change in condition				
Boiling point/Boiling range:	137 °C			
· Flash point:	30 °C			
· Flammability (solid, gaseous):	Not applicable.			
· Ignition temperature:	340 °C			
· Decomposition temperature:	Not determined.			
· Self-igniting:	Product is not selfigniting.			
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.			
· Explosion limits:				
Lower:	1.1 Vol %			
Upper:	7.0 Vol %			
· Vapour pressure at 20 °C:	6.7 hPa			
· Density at 20 °C:	0.94099 g/cm³			
· Relative density	Not determined.			
· Vapour density	Not determined.			
· Evaporation rate	Not determined.			
· Solubility in / Miscibility with				
water:	Not miscible or difficult to mix.			





Vers.-Nr: 53 Revision: 23.05.2023

Trade name: Transpoxy ZP primer 1.61 pack B

(Contd. of page 4)

· Partition coefficient (n-octanol/water): Not determined. · Viscosity: Dynamic at 20 °C: 2000 mPas Kinematic: Not determined. · Solvent content: VOC (EC) 374.5 g/l · Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

Information Acute tox	on on toxicological icity	al (effects
· LD/LC50 values relevant for			classification:
1330-20-7	xylene, mixture	of i	somers
Oral	LD50		>2000 mg/kg (rat)
	LC50/ 96 hr (stati	,	2.6 mg/l (Rainbow trout (Oncorhynchus mykiss)) (OESO 203 or equivalent)
Dermal	LD50		>2000 mg/kg (rabbit)
Inhalative	LC50/4 h		>20 mg/l (rat)

- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Serious eye damage/irritation Strong irritant with the danger of severe eye injury.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful Irritant

(Contd. on page 7)





Vers.-Nr: 53 Revision: 23.05.2023

Trade name: Transpoxy ZP primer 1.61 pack B

(Contd. of page 4)

12 Ecological information

- · Toxicity
- Aguatic toxicity:

1330-20-7 xylene, mixture of isomers

EC 50 (48 hr) 1-10 mg/l (daphnia) EC 50 (72 hr) 1-10 mg/l (Algae)

- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

Void UN1263	
Void Paint	
Void	
	UN1263 Void Paint





Vers.-Nr: 53 Revision: 23.05.2023

Trade name: Transpoxy ZP primer 1.61 pack B

(Contd. of page 4)

· IATA				
· Class	3 Flammable liquids.			
· Label	3			
· Packing group				
· ADG, IMDG	Void			
· IATA	III			
· Environmental hazards:				
· Marine pollutant:	No			
· Special precautions for user	Not applicable.			
· Transport in bulk according to Annex II of				
Marpol and the IBC Code	Not applicable.			
· UN "Model Regulation":	Void			

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Australian Inventory of Chemical Substances
 All ingredients are listed.

 Standard for the Uniform Scheduling of Medicines and Poisons
 1330-20-7 | xylene, mixture of isomers | S6
- · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms





GHS02 GHS05

- · Signal word Danger
- Hazard-determining components of labelling:

reaction product based on fatty acids and polyethyleneamine

xylene, mixture of isomers

butan-1-ol

· Hazard statements

Flammable liquid and vapour.

Causes skin irritation.

Causes serious eye damage.

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 9)



Page 9/9

Safety data sheet according to WHS Regulations

Revision: 23.05.2023 Vers.-Nr: 53

Trade name: Transpoxy ZP primer 1.61 pack B

(Contd. of page 4)

Use explosion-proof electrical/ventilating/lighting/equipment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

· * Data compared to the previous version altered.