

Page 1/9

# Safety data sheet according to WHS Regulations

Vers.-Nr: 55

Revision: 23.05.2023

Hazardous according to criteria of Australian Safety and Compensation Council

## **1 Identification**

- · Product identifier
- · Trade name: Transpoxy MIO primer 1.64 pack B
- · Article number: 164b
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- Application of the substance/preparation: Epoxy curing agent Paint
- · Details of the supplier of the safety data sheet
- Manufacturer/supplier: Transocean Coatings Wagon Paints Australia Pty Ltd ABN: 76 412 791 772 Street address: 5 Stephenson Road, Bayswater North VIC, 3153 Australia Phone: +613 9729-1344 Fax: +613 9720 2719
- Further information obtainable from: Product safety department.
- · Emergency telephone number:
- Medical Emergencies: 24 Hours
- Poisons Information Centre (Australia): 131 126

## **2 Hazard Identification**

### · Classification of the substance or mixture

Flam. Liq. 3 H226 Flammable liquid and vapour.

- Skin Irrit. 2 H315 Causes skin irritation.
- Eye Dam. 1 H318 Causes serious eye damage.
- · Label elements
- · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS). • Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labelling:
- reaction product based on fatty acids and polyethyleneamine xylene, mixture of isomers butan-1-ol
- **Hazard statements** Flammable liquid and vapour. Causes skin irritation.



Page 2/9

# Safety data sheet according to WHS Regulations

Vers.-Nr: 55

Revision: 23.05.2023

### Trade name: Transpoxy MIO primer 1.64 pack B

(Contd. of page 1)

## Causes serious eye damage.

Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical/ventilating/lighting/equipment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Dispose of contents/container in accordance with local/regional/national/international regulations. • Other hazards

#### · Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

## **3 Composition and information on ingredients**

### · Chemical characterisation: Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

68410-23-1	reaction product based on fatty acids and polyethyleneamine				
	Eye Dam. 1, H318				
1330-20-7	xylene, mixture of isomers				
	Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315				
	butan-1-ol	2,5-10%			
	Flam. Liq. 3, H226; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336				

• Additional information: For the wording of the listed risk phrases refer to section 16.

### **4 First Aid Measures**

### Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

- · After eye contact:
- Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- $\cdot$  Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)



Page 3/9

## Safety data sheet according to WHS Regulations

Vers.-Nr: 55

Revision: 23.05.2023

(Contd. of page 2)

### Trade name: Transpoxy MIO primer 1.64 pack B

• Indication of any immediate medical attention and special treatment needed No further relevant information available.

## **5 Fire Fighting Measures**

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- $\cdot$  Special hazards arising from the substance or mixture
- No further relevant information available.
- · Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

### 6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.
   Ensure adequate ventilation.
   Do not fluck with water or acupate cleansing agents.
- Do not flush with water or aqueous cleansing agents
- Reference to other sections See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

- · Handling:
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Specific end use(s) No further relevant information available.

### 8 Exposure controls and personal protection

• Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)



Page 4/9

# Safety data sheet according to WHS Regulations

Vers.-Nr: 55

Revision: 23.05.2023

### Trade name: Transpoxy MIO primer 1.64 pack B

(Contd. of page 3)

· Cont	· Control parameters					
· Ingre	$\cdot$ Ingredients with limit values that require monitoring at the workplace:					
	1330-20-7 xylene, mixture of isomers					
NES			m value: 655 mg/m³, 150 ppm m value: 350 mg/m³, 80 ppm			
71-36	71-36-3 butan-1-ol					
NES	Peak Sk	k limitation: 152 mg/m³, 50 ppm				
· DNEI	· DNELs					
1330-	-20-7	xylen	e, mixture	of isomers		
Derm	al	long t	erm DNEL	108 mg/kg/d (General Population)		
				180 mg/kg/d (Workers)		
Inhala	ative	long term DNEL		14.8 mg/m3 (General Population)		
				77 mg/m3 (Workers)		
· PNEC	Cs					
1330-	-20-7	xylen	e, mixture	of isomers		
PNEC	C STF	)	6.58 mg/l (water treatment plant)			
PNEC	PNEC aqua		327 ug/l (freshwater)			
			327 ug/l (marine water)			
PNEC	C sedi	iment	12.46 mg/kg (freshwater)			
			12.46 mg/kg (marine water)			
PNEC	PNEC soil 2.31 mg/k		2.31 mg/kg	y (Soil)		
	Additional information. The lists valid during the making ware used as basis					

 $\cdot$  Additional information: The lists valid during the making were used as basis.

### · Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5) AU



# Safety data sheet according to WHS Regulations

Vers.-Nr: 55

Revision: 23.05.2023

### Trade name: Transpoxy MIO primer 1.64 pack B

(Contd. of page 4)

• Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed gog<del>gles</del>

## **9 Physical and chemical properties**

<ul> <li>Information on basic physical ar</li> <li>General Information</li> </ul>	nd chemical properties
<ul> <li>Appearance:</li> <li>Form:</li> <li>Colour:</li> <li>Odour:</li> <li>Odour threshold:</li> </ul>	Fluid According to product specification Characteristic Not determined.
· pH-value:	Not determined.
<ul> <li>Change in condition Boiling point/Boiling range:</li> </ul>	137 °C
· Flash point:	30 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	340 °C
<ul> <li>Decomposition temperature:</li> </ul>	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits: Lower: Upper:	1.1 Vol % 7.0 Vol %
· Vapour pressure at 20 °C:	6.7 hPa
<ul> <li>Density at 20 °C:</li> <li>Relative density</li> <li>Vapour density</li> <li>Evaporation rate</li> </ul>	0.94 g/cm <sup>3</sup> Not determined. Not determined. Not determined.
<ul> <li>Solubility in / Miscibility with water:</li> </ul>	Not miscible or difficult to mix.



Page 6/9

## Safety data sheet according to WHS Regulations

Vers.-Nr: 55

Revision: 23.05.2023

### Trade name: Transpoxy MIO primer 1.64 pack B

(Contd. of page 4)

· Partition coefficient (n-octanol/water): Not determined.			
· Viscosity:			
Dynamic at 20 °C:	2500 mPas		
Kinematic:	Not determined.		
· Solvent content:			
VOC (EC)	376.0 g/l		
· Other information	No further relevant information available.		

## **10 Stability and reactivity**

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

## **11 Toxicological information**

- · Information on toxicological effects
- · Acute toxicity

· LD/LC50 \	/alues relevant f	or c	lassification:
1330-20-7 xylene, mixture			somers
Oral	LD50		>2000 mg/kg (rat)
	LC50/ 96 hr (stat		2.6 mg/l (Rainbow trout (Oncorhynchus mykiss)) (OESO 203 or equivalent)
Dermal	LD50		>2000 mg/kg (rabbit)
Inhalative	LC50/4 h		>20 mg/l (rat)
Primary irritant effect			

- · Primary irritant effect:
- Skin corrosion/irritation Irritant to skin and mucous membranes.
- Serious eye damage/irritation Strong irritant with the danger of severe eye injury.
- Respiratory or skin sensitisation No sensitising effects known.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful Irritant

(Contd. on page 7)



Safety data sheet according to WHS Regulations

Vers.-Nr: 55

Revision: 23.05.2023

### Trade name: Transpoxy MIO primer 1.64 pack B

(Contd. of page 4)

Page 7/9

## **12 Ecological information**

- · Toxicity
- Aquatic toxicity:

### 1330-20-7 xylene, mixture of isomers

- EC 50 (48 hr) 1-10 mg/l (daphnia)
- EC 50 (72 hr) 1-10 mg/l (Algae)
- Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:

#### · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

### **13 Disposal considerations**

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

· UN-Number · ADG, ADN, IMDG · IATA	Void UN1263	
<ul> <li>UN proper shipping name</li> <li>ADG, ADN, IMDG</li> <li>IATA</li> </ul>	Void Paint	
· Transport hazard class(es)		
· ADG, ADN, IMDG · Class	Void	



Page 8/9

## Safety data sheet according to WHS Regulations

Vers.-Nr: 55

Revision: 23.05.2023

### Trade name: Transpoxy MIO primer 1.64 pack B

(Contd. of page 4)

· Class	3 Flammable liquids.	
· Label	3	
· Packing group		
· ADG, IMDG	Void	
· IATA	III	
· Environmental hazards:		
· Marine pollutant:	No	
<ul> <li>Special precautions for user</li> </ul>	Not applicable.	
<ul> <li>Transport in bulk according to Annex Marpol and the IBC Code</li> </ul>	II of Not applicable.	
· UN "Model Regulation":	Void	

## **15 Regulatory information**

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Australian Inventory of Chemical Substances

   All ingredients are listed.

   Standard for the Uniform Scheduling of Medicines and Poisons

   1330-20-7
   xylene, mixture of isomers
  - · GHS label elements
  - The product is classified and labelled according to the Globally Harmonised System (GHS).
  - Hazard pictograms



- · Signal word Danger
- Hazard-determining components of labelling: reaction product based on fatty acids and polyethyleneamine xylene, mixture of isomers butan-1-ol
- **Hazard statements** Flammable liquid and vapour. Causes skin irritation. Causes serious eye damage.
- **Precautionary statements** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 9)

<sup>-</sup>AU-



Page 9/9

## Safety data sheet according to WHS Regulations

Vers.-Nr: 55

Revision: 23.05.2023

### Trade name: Transpoxy MIO primer 1.64 pack B

(Contd. of page 4)

Use explosion-proof electrical/ventilating/lighting/equipment. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF IN EYES: Rinse cautious y with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Central Office.
- · Contact: Central Office
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids, Hazard Category 3 Acute Tox. 4: Acute toxicity, Hazard Category 4 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3  $\cdot$  \* Data compared to the previous version altered.