



Vers.-Nr: 51 Revision: 23.05.2023

Hazardous according to criteria of Australian Safety and Compensation Council

1 Identification

· Product identifier

· Trade name: Transpoxy Barrier 2.18 pack B

· Article number: 218b

· Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance/preparation:

Epoxy curing agent

Paint

· Details of the supplier of the safety data sheet

· Manufacturer/supplier:

Transocean Coatings

Wagon Paints Australia Pty Ltd

ABN: 76 412 791 772

Street address: 5 Stephenson Road, Bayswater North

VIC, 3153 Australia Phone: +613 9729-1344 Fax: +613 9720 2719

· Emergency telephone number:

· Medical Emergencies: 24 Hours

· Poisons Information Centre (Australia): 131 126

2 Hazard Identification

· Classification of the substance or mixture

Flam. Liq. 3 H226 Flammable liquid and vapour.

Acute Tox. 4 H302 Harmful if swallowed. Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms







GHS02 GHS05 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

reaction product based on fatty acids and polyethyleneamine butan-1-ol

3,6-diazaoctanethylenediamin





Vers.-Nr: 51 Revision: 23.05.2023

Trade name: Transpoxy Barrier 2.18 pack B

(Contd. of page 1)

· Hazard statements

Flammable liquid and vapour.

Harmful if swallowed.

Causes skin irritation.

Causes serious eye damage.

May cause an allergic skin reaction.

May cause respiratory irritation. May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition and information on ingredients

- · Chemical characterisation: Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

	 Dangerous 	components:		
68410-23-1 reaction produc		reaction produc	t based on fatty acids and polyethyleneamine	50-100%
		Eye Dam. 1	, H318	
71-36-3 butan-1-ol				10-25%
		Flam. Liq. 3 Irrit. 2, H315; S	, H226; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin TOT SE 3, H335-H336	
ſ	112-24-3 3,6-diazaoctanethylenediam		ethylenediamin	2,5-10%
		Skin Corr. 1 Sens. 1, H317	B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin	

[·] Additional information: For the wording of the listed risk phrases refer to section 16.

4 First Aid Measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing: Call for a doctor immediately.

(Contd. on page 3)





Vers.-Nr: 51 Revision: 23.05.2023

Trade name: Transpoxy Barrier 2.18 pack B

(Contd. of page 2)

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

No further relevant information available.

- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

ΔΙ





Vers.-Nr: 51 Revision: 23.05.2023

Trade name: Transpoxy Barrier 2.18 pack B

(Contd. of page 3)

8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

· Ingredien	· Ingredients with limit values that require monitoring at the workplace:			
71-36-3 b	71-36-3 butan-1-ol			
NES Pea Sk	NES Peak limitation: 152 mg/m³, 50 ppm Sk			
DNELs	DNELs			
71-36-3 b	71-36-3 butan-1-ol			
Oral	long t	erm DNEL	3125 mg/kg/d (General Population)	
Inhalative	long t	erm DNEL	55 mg/m3 (General Population)	
			310 mg/m3 (Workers)	
· PNECs	PNECs			
71-36-3 b	71-36-3 butan-1-ol			
PNEC ST	PNEC STP 2476 mg/l		(water treatment plant)	
			2.25 mg/l (intermittent release)	
PNEC aqu	ıa	8.2 ug/l (marine water)		
PNEC sec	PNEC sediment 0.178 mg/kg 0.0178 mg/kg PNEC soil 0.015 mg/kg		0.178 mg/kg (freshwater)	
			0.0178 mg/kg (marine water)	
PNEC soil			kg (Soil)	

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has





Vers.-Nr: 51 Revision: 23.05.2023

Trade name: Transpoxy Barrier 2.18 pack B

(Contd. of page 4)

therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

 Information on basic physical and chemical properties General Information Appearance: Form: Colour: Odour: Odour threshold: pH-value: Change in condition Boiling point/Boiling range: Information on basic physical and chemical properties Fluid According to product specification Characteristic Not determined. Not determined. 150 °C	
 Appearance: Form: Colour: According to product specification Characteristic Not determined. pH-value: Not determined. 	
Form: Colour: Odour: Odour: Odour threshold: PH-value: Change in condition Fluid According to product specification Characteristic Not determined. Not determined.	
Colour: Odour: Odour: Odour threshold: O	
 Odour: Characteristic Odour threshold: Not determined. pH-value: Not determined. Change in condition 	
 Odour threshold: Not determined. pH-value: Not determined. Change in condition 	
 pH-value: Not determined. Change in condition 	
· Change in condition	
Boiling point/Boiling range: 150 °C	
· Flash point: 35 °C	
· Flammability (solid, gaseous): Not applicable.	
· Ignition temperature: 340 °C	
· Decomposition temperature: Not determined.	
· Self-igniting: Product is not selfigniting.	
 Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible. 	ıf
· Explosion limits:	
Lower: 1.5 Vol %	
Upper: 9.4 Vol %	
· Vapour pressure at 20 °C: 6.7 hPa	
· Density at 20 °C: 0.96 g/cm³	
• Relative density Not determined.	
· Vapour density Not determined.	
· Evaporation rate Not determined.	
· Solubility in / Miscibility with	
water: Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water): Not determined.	
· Viscosity:	
Dynamic: Not determined.	





Vers.-Nr: 51 Revision: 23.05.2023

Trade name: Transpoxy Barrier 2.18 pack B

(Contd. of page 5)

Kinematic:	Not determined.
· Solvent content: VOC (EC)	211.2 g/l
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

· LD/LC50 values relevant f			or classification:
71-36-3 butan-1-ol			
Oral	LD50	229	2 mg/kg (rat)
	LC50/ 96 hr	137	6 mg/l (fish)
Dermal	LD50	340	0 mg/kg (rabbit)
Inhalative	LC50/4 h	17.	76 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Serious eye damage/irritation Strong irritant with the danger of severe eye injury.
- · Respiratory or skin sensitisation Sensitisation possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

12 Ecological information

· Toxicity

· Aquatic toxicity:					
71-36-3 butan-1-ol					
EC 50 (48 hr)	1328 mg/l (daphnia)				





Vers.-Nr: 51 Revision: 23.05.2023

Trade name: Transpoxy Barrier 2.18 pack B

(Contd. of page 6)

- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

UN1263
1263 PAINT, special provision 640E PAINT Paint
2 Florereable limitele
3 Flammable liquids. 3
III
No
Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
(Contd. on page 8





Vers.-Nr: 51 Revision: 23.05.2023

Trade name: Transpoxy Barrier 2.18 pack B

(Contd. of page 6)

	(Coma. or page o
 Transport in bulk according to Anne Marpol and the IBC Code 	x II of Not applicable.
· Transport/Additional information:	
· ADG	
 Limited quantities (LQ) 	5L
· Excepted quantities (ÉQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
	-,_
· IMDG	
· Limited quantities (LQ)	5L
 Excepted quantities (EQ) 	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, SPECIAL PROVISION 640E, 3, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Australian Inventory of Chemical Substances

All ingredients are listed.

· Standard for the Uniform Scheduling of Medicines and Poisons

None of the ingredients is listed.

· GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms







GHS02 GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

reaction product based on fatty acids and polyethyleneamine butan-1-ol

3,6-diazaoctanethylenediamin

· Hazard statements

Flammable liquid and vapour.

Harmful if swallowed.

Causes skin irritation.

Causes serious eye damage.

May cause an allergic skin reaction.

May cause respiratory irritation. May cause drowsiness or dizziness.





Vers.-Nr: 51 Revision: 23.05.2023

Trade name: Transpoxy Barrier 2.18 pack B

(Contd. of page 6)

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. IF ON SKIN (or hair): Takeroff immediately all contaminated clothing. Rinse skin with water/ shower.

IF IN EYES: Rinse cautious with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

· * Data compared to the previous version altered.