

## Safety data sheet according to WHS Regulations

Vers.-Nr: 55


Revision: 23.05.2023

Hazardous according to criteria of Australian Safety and Compensation Council

### 1 Identification

- **Product identifier**
- **Trade name:** Transpoxy Intermediate 2.19 pack A
- **Article number:** 219a
- **Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance/preparation:**  
Epoxy coating  
Paint
- **Details of the supplier of the safety data sheet**
- **Manufacturer/supplier:**  
Transocean Coatings  
Wagon Paints Australia Pty Ltd  
ABN: 76 412 791 772  
Street address: 5 Stephenson Road, Bayswater North  
VIC, 3153 Australia  
Phone: +613 9729-1344  
Fax: +613 9720 2719
- **Emergency telephone number:**
- Medical Emergencies: 24 Hours
- Poisons Information Centre (Australia): 131 126

### 2 Hazard Identification

- **Classification of the substance or mixture**  
Flam. Liq. 3 H226 Flammable liquid and vapour.  
Acute Tox. 3 H331 Toxic if inhaled.  
Skin Irrit. 2 H315 Causes skin irritation.  
Eye Irrit. 2 H319 Causes serious eye irritation.  
Skin Sens. 1 H317 May cause an allergic skin reaction.  
Muta. 1B H340 May cause genetic defects.  
Carc. 1B H350 May cause cancer.
- **Label elements**
- **GHS label elements**  
The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**  
  
GHS02 GHS06 GHS08
- **Signal word** Danger
- **Hazard-determining components of labeling:**  
xylene, mixture of isomers

(Contd. on page 2)  
AU

## Safety data sheet according to WHS Regulations

Vers.-Nr: 55

Revision: 23.05.2023

**Trade name: Transpoxy Intermediate 2.19 pack A**

(Contd. of page 1)

reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight > 700)

Solvent naphtha (petroleum), light arom.

4-methylpentan-2-one

• **Hazard statements**

Flammable liquid and vapour.

Toxic if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

• **Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

• **Other hazards**

• **Results of PBT and vPvB assessment**

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

### 3 Composition and information on ingredients

• **Chemical characterisation: Mixtures**

• **Description:** Mixture of substances listed below with nonhazardous additions.

• **Dangerous components:**

25036-25-3	reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight > 700) Skin Sens. 1, H317	10-25%
1330-20-7	xylene, mixture of isomers Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	10-25%
64742-95-6	Solvent naphtha (petroleum), light arom. Flam. Liq. 1, H224; Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304	2,5-10%
108-10-1	4-methylpentan-2-one Flam. Liq. 2, H225; Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	2,5-10%
12001-26-2	Mica	2,5-10%
67-63-0	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	≤ 2,5%
107-98-2	1-methoxy-2-propanol Flam. Liq. 3, H226; STOT SE 3, H336	≤ 2,5%
7631-86-9	silicon dioxide, chemically prepared Acute Tox. 2, H330	≤ 2,5%

(Contd. on page 3)

AU

## Safety data sheet according to WHS Regulations

Vers.-Nr: 55

Revision: 23.05.2023

**Trade name: Transpoxy Intermediate 2.19 pack A**

(Contd. of page 2)

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

### 4 First Aid Measures

- **Description of first aid measures**
- **General information:**  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire Fighting Measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**  
No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

AU

(Contd. on page 4)

## Safety data sheet according to WHS Regulations

Vers.-Nr: 55

Revision: 23.05.2023

Trade name: Transpoxy Intermediate 2.19 pack A

(Contd. of page 3)

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

<b>1330-20-7 xylene, mixture of isomers</b>	
NES	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 350 mg/m <sup>3</sup> , 80 ppm
<b>108-10-1 4-methylpentan-2-one</b>	
NES	Short-term value: 307 mg/m <sup>3</sup> , 75 ppm Long-term value: 205 mg/m <sup>3</sup> , 50 ppm
<b>12001-26-2 Mica</b>	
NES	Long-term value: 2.5 mg/m <sup>3</sup>
<b>67-63-0 propan-2-ol</b>	
NES	Short-term value: 1230 mg/m <sup>3</sup> , 500 ppm Long-term value: 983 mg/m <sup>3</sup> , 400 ppm
<b>107-98-2 1-methoxy-2-propanol</b>	
NES	Short-term value: 553 mg/m <sup>3</sup> , 150 ppm Long-term value: 369 mg/m <sup>3</sup> , 100 ppm

- **Additional information:** The lists valid during the making were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.

- **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

AU

## Safety data sheet according to WHS Regulations

Vers.-Nr: 55

Revision: 23.05.2023

**Trade name: Transpoxy Intermediate 2.19 pack A**

(Contd. of page 4)

• **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye protection:**



Tightly sealed goggles

### 9 Physical and chemical properties

• **Information on basic physical and chemical properties**

• **General Information**

• **Appearance:**

Form:

Fluid

Colour:

According to product specification

• **Odour:**

Characteristic

• **Odour threshold:**

Not determined.

• **pH-value:**

Not determined.

• **Change in condition**

Boiling point/Boiling range:

114 °C

• **Flash point:**

26 °C

• **Flammability (solid, gaseous):**

Not applicable.

• **Ignition temperature:**

500 °C

• **Decomposition temperature:**

Not determined.

• **Self-igniting:**

Product is not selfigniting.

• **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 6)

AU

## Safety data sheet according to WHS Regulations

Vers.-Nr: 55

Revision: 23.05.2023

Trade name: Transpoxy Intermediate 2.19 pack A

(Contd. of page 4)

· <b>Explosion limits:</b>	
<b>Lower:</b>	1.1 Vol %
<b>Upper:</b>	7.0 Vol %
· <b>Vapour pressure at 20 °C:</b>	6.7 hPa
· <b>Density at 20 °C:</b>	1.45482 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>VOC (EC)</b>	336.9 g/l
· <b>Other information</b>	No further relevant information available.

\*

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

\*

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**
- **Primary irritant effect:**
- **Skin corrosion/irritation** Irritant to skin and mucous membranes.
- **Serious eye damage/irritation** Irritating effect.
- **Respiratory or skin sensitisation** Sensitisation possible through skin contact.
- **Additional toxicological information:**  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Harmful  
Irritant

AU

(Contd. on page 7)

## Safety data sheet according to WHS Regulations

Vers.-Nr: 55

Revision: 23.05.2023

Trade name: Transpoxy Intermediate 2.19 pack A

(Contd. of page 4)


### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

<ul style="list-style-type: none"> <li>• <b>UN-Number</b></li> <li>• <b>ADG, IMDG, IATA</b></li> </ul>	UN1263
<ul style="list-style-type: none"> <li>• <b>UN proper shipping name</b></li> <li>• <b>ADG</b></li> <li>• <b>IMDG</b></li> <li>• <b>IATA</b></li> </ul>	1263 PAINT, special provision 640E PAINT Paint
<ul style="list-style-type: none"> <li>• <b>Transport hazard class(es)</b></li> <li>• <b>ADG, IMDG, IATA</b></li> </ul>  <ul style="list-style-type: none"> <li>• <b>Class</b></li> <li>• <b>Label</b></li> </ul>	3 Flammable liquids. 3
<ul style="list-style-type: none"> <li>• <b>Packing group</b></li> <li>• <b>ADG, IMDG, IATA</b></li> </ul>	III

(Contd. on page 8)

AU

## Safety data sheet according to WHS Regulations

Vers.-Nr: 55

Revision: 23.05.2023

Trade name: Transpoxy Intermediate 2.19 pack A

(Contd. of page 4)

· <b>Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b>	Warning: Flammable liquids.
· <b>Danger code (Kemler):</b>	30
· <b>EMS Number:</b>	F-E, S-E
· <b>Stowage Category</b>	A
· <b>Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>Transport category</b>	3
· <b>Tunnel restriction code</b>	D/E
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 1263 PAINT, SPECIAL PROVISION 640E, 3, III

### 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Australian Inventory of Chemical Substances**

14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )
25036-25-3	reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight > 700)
13463-67-7	titanium dioxide
1330-20-7	xylene, mixture of isomers
108-10-1	4-methylpentan-2-one
12001-26-2	Mica
67-63-0	propan-2-ol
107-98-2	1-methoxy-2-propanol
7631-86-9	silicon dioxide, chemically prepared
	Quaternary ammonium compounds, benzyl( hydrogenated tallow alkyl) dimethyl, chlorides, compds. with hectorite
64-17-5	ethanol

· **Standard for the Uniform Scheduling of Medicines and Poisons**

1330-20-7	xylene, mixture of isomers	S6
-----------	----------------------------	----

(Contd. on page 9)

AU

## Safety data sheet according to WHS Regulations

Vers.-Nr: 55

Revision: 23.05.2023

**Trade name: Transpoxy Intermediate 2.19 pack A**

(Contd. of page 4)

108-10-1	4-methylpentan-2-one	S5
----------	----------------------	----

• **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

• **Hazard pictograms**



GHS02 GHS06 GHS08

• **Signal word** Danger

• **Hazard-determining components of labelling:**

xylene, mixture of isomers

reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight > 700)

Solvent naphtha (petroleum), light arom.

4-methylpentan-2-one

• **Hazard statements**

Flammable liquid and vapour.

Toxic if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

• **Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

• **Directive 2012/18/EU**

• **Named dangerous substances - ANNEX I** None of the ingredients is listed.

• **Seveso category**

H2 ACUTE TOXIC

P5c FLAMMABLE LIQUIDS

• **Qualifying quantity (tonnes) for the application of lower-tier requirements** 50 t

• **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t

• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 10)

AU

## Safety data sheet according to WHS Regulations

Vers.-Nr: 55

Revision: 23.05.2023

**Trade name: Transpoxy Intermediate 2.19 pack A**

(Contd. of page 9)

ICAO: International Civil Aviation Organisation  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
VOC: Volatile Organic Compounds (USA, EU)  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Liq. 1: Flammable liquids, Hazard Category 1  
Flam. Liq. 2: Flammable liquids, Hazard Category 2  
Flam. Liq. 3: Flammable liquids, Hazard Category 3  
Acute Tox. 4: Acute toxicity, Hazard Category 4  
Acute Tox. 2: Acute toxicity, Hazard Category 2  
Acute Tox. 3: Acute toxicity, Hazard Category 3  
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2  
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1  
Muta. 1B: Germ cell mutagenicity, Hazard Category 1B  
Carc. 1B: Carcinogenicity, Hazard Category 1B  
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3  
Asp. Tox. 1: Aspiration hazard, Hazard Category 1

• **\* Data compared to the previous version altered.**

AU