



Vers.-Nr: 56 Revision: 23.05.2023

Hazardous according to criteria of Australian Safety and Compensation Council

### 1 Identification

· Product identifier

· Trade name: Transolac Finish QD 3.33

· Article number: 333-2

· Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance/preparation:

Solvent-based synthetic resin paint

**Paint** 

· Details of the supplier of the safety data sheet

· Manufacturer/supplier:

Transocean Coatings

Wagon Paints Australia Pty Ltd

ABN: 76 412 791 772

Street address: 5 Stephenson Road, Bayswater North

VIC, 3153 Australia Phone: +613 9729-1344 Fax: +613 9720 2719

· Emergency telephone number:

· Medical Emergencies: 24 Hours

· Poisons Information Centre (Australia): 131 126

### 2 Hazard Identification

· Classification of the substance or mixture

Flam. Lig. 3 H226 Flammable liquid and vapour.

Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

- · Label elements
- · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

xylene, mixture of isomers

Barium octoate

ethyl acrylate-2-ehtylhexyl acrylate copolymer

· Hazard statements

Flammable liquid and vapour.

Harmful if inhaled.



Vers.-Nr: 56 Revision: 23.05.2023

Trade name: Transolac Finish QD 3.33

(Contd. of page 1)

Causes skin irritation.

Causes serious eye irritation.

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical/ventilating/lighting/equipment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautious y with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

# 3 Composition and information on ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous	components:		
1330-20-7	-7 xylene, mixture of isomers		
	Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315		
64742-95-6	Solvent naphtha (petroleum), light arom.	10-25%	
	Asp. Tox. 1, H304; STOT SE 3, H335-H336; Flam. Liq. 4, H227		
7727-43-7	barium sulphate, precipitated	2,5-10%	
71-36-3	butan-1-ol	≤ 2,5%	
	Flam. Liq. 3, H226; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336		
96-29-7	2-butanone oxime	≤ 2,5%	
	Carc. 2, H351; Eye Dam. 1, H318; Acute Tox. 4, H312; Skin Sens. 1, H317; Flam. Liq. 4, H227		
68409-81-4	Cobalt soap of C6-C19 fatty acids	≤ 2,5%	
	Acute Tox. 3, H301; Skin Irrit. 2, H315; Skin Sens. 1, H317		
149-57-5	2-ethylhexanoic acid	≤ 2,5%	
	Repr. 2, H361		

<sup>·</sup> Additional information: For the wording of the listed risk phrases refer to section 16.

# **4 First Aid Measures**

- · Description of first aid measures
- · After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)



Page 3/10

# Safety data sheet according to WHS Regulations

Vers.-Nr: 56 Revision: 23.05.2023

Trade name: Transolac Finish QD 3.33

(Contd. of page 2)

- · Information for doctor:
- Most important symptoms and effects, both acute and delayed
   No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

### **5 Fire Fighting Measures**

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

No further relevant information available.

- · Advice for firefighters
- · Protective equipment: No special measures required.

### 6 Accidental release measures

 $\cdot$  Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

- · Reference to other sections
  - See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# 7 Handling and storage

- · Handling:
- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

ΑL





Vers.-Nr: 56 Revision: 23.05.2023

Trade name: Transolac Finish QD 3.33

(Contd. of page 3)

### 8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

· Control parameters					
· Ingredients	· Ingredients with limit values that require monitoring at the workplace:				
1330-20-7 x	1330-20-7 xylene, mixture of isomers				
		mg/m³, 150 ppm			
	ong-term value: 350 mg/m³, 80 ppm				
	parium sulphate				
	term value: 10 n	ng/m³			
71-36-3 but					
NES Peak I Sk	limitation: 152 m	ng/m³, 50 ppm			
· DNELs					
1330-20-7 x	ylene, mixture	of isomers			
Dermal lo	ong term DNEL	108 mg/kg/d (General Population)			
		180 mg/kg/d (Workers)			
Inhalative lo	ong term DNEL	14.8 mg/m3 (General Population)			
		77 mg/m3 (Workers)			
	5-6 Solvent naphtha (petroleum), light arom.				
Oral lo	ong term DNEL	11 mg/kg/d (General Population)			
Dermal lo	ong term DNEL	11 mg/kg/d (General Population)			
		25 mg/kg/d (Workers)			
Inhalative lo	ong term DNEL	32 mg/m3 (General Population)			
		150 mg/m3 (Workers)			
· PNECs					
	-7 xylene, mixture of isomers				
PNEC STP	6.58 mg/l (	(water treatment plant)			
PNEC aqua	327 ug/l (fi	reshwater)			
	327 ug/l (n	narine water)			
PNEC sedin	ment 12.46 mg/l	kg (freshwater)			
	12.46 mg/l	kg (marine water)			
PNEC soil 2.31 mg/k		g (Soil)			

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- Personal protective equipment:
- $\cdot$  General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.





Vers.-Nr: 56 Revision: 23.05.2023

Trade name: Transolac Finish QD 3.33

(Contd. of page 4)

### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Information on basic physical and	chemical properties	
General Information		
· Appearance:		
Form:	Fluid	
Colour:	According to product specification	
· Odour:	Characteristic	
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
Change in condition		
Boiling point/Boiling range:	137 °C	
· Flash point:	30 °C	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	450 °C	
Decomposition temperature:	Not determined.	
· Self-igniting:	Product is not selfigniting.	





Vers.-Nr: 56 Revision: 23.05.2023

Trade name: Transolac Finish QD 3.33

(Contd. of page 4)

	(Conta. or page -	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.	
· Explosion limits:		
Lower:	0.7 Vol %	
Upper:	7.5 Vol %	
· Vapour pressure at 20 °C: 6.7 hPa		
• Density at 20 °C: 1.23336 g/cm³		
Relative density	Not determined.	
Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water): Not determined.		
· Viscosity:		
Dynamic at 20 ℃:	800 mPas	
Kinematic:	Not determined.	
· Solvent content:		
VOC (EC)	457.1 g/l	
· Other information	No further relevant information available.	

# 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information · Information on toxicological effects · Acute toxicity · LD/LC50 values relevant for classification: 1330-20-7 xylene, mixture of isomers Oral LD50 >2000 mg/kg (rat) LC50/ 96 hr (static) 2.6 mg/l (Rainbow trout (Oncorhynchus mykiss)) (OESO 203 or equivalent) Dermal LD50 >2000 mg/kg (rabbit) Inhalative LC50/4 h >20 mg/l (rat) (Contd. on page 7)

Αl





Vers.-Nr: 56 Revision: 23.05.2023

Trade name: Transolac Finish QD 3.33

(Contd. of page 4)

	64742-95-6 Solvent naphtha (petroleum), light arom.				
Oral LD50 3492 mg/k		LD50	3492 mg/kg (rat)		
LC50/ 96 hr		LC50/ 96 hr	9.2 mg/l (Rainbow trout (Oncorhynchus mykiss))		
Dermal LD50		LD50	>3160 mg/kg (rab)		
	Inhalative	LC50/4 h	>6193 mg/l (rat)		

- Primary irritant effect:
- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

# 12 Ecological information

· Toxicity

· Aquatic toxic	ity:		
1330-20-7 xyl	ene, mixture of isomers		
EC 50 (48 hr)	1-10 mg/l (daphnia)		
EC 50 (72 hr)	1-10 mg/l (Algae)		
64742-95-6 Sc	64742-95-6 Solvent naphtha (petroleum), light arom.		
EC 50 (48 hr)	3.2 mg/l (daphnia)		
EC 50 (72 hr)	2.9 mg/l (Algae)		

- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)





Vers.-Nr: 56 Revision: 23.05.2023

Trade name: Transolac Finish QD 3.33

(Contd. of page 4)

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information	
<ul><li>UN-Number</li><li>ADG, ADN, IMDG</li><li>IATA</li></ul>	Void UN1263
<ul><li>UN proper shipping name</li><li>ADG, ADN, IMDG</li><li>IATA</li></ul>	Void Paint
· Transport hazard class(es)	
· ADG, ADN, IMDG · Class	Void
· IATA	
· Class	3 Flammable liquids.
· Label	3
· Packing group	
· ADG, IMDG	Void
· IATA	III
· Environmental hazards:	
· Marine pollutant:	No

· Special precautions for user Not applicable.

· Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

· UN "Model Regulation": Void

# 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Ch	emical Substances
1330-20-7 xylene, mixture	of isomers
13463-67-7 titanium dioxide	)
7727-43-7 barium sulphate	e, precipitated
71-36-3 butan-1-ol	
64742-48-9 Hydrocarbons, (	C10-C13, n-alkanes, isoalkanes, cuclics, <2% aromatics
96-29-7 2-butanone oxin	me
	(Contd. on page 9





Vers.-Nr: 56 Revision: 23.05.2023

Trade name: Transolac Finish QD 3.33

(	Conto	. of	pa	qе	4

	(Conta:	or page 17	
149-57-5	2-ethylhexanoic acid		
26376-86-3	ethyl acrylate-2-ehtylhexyl acrylate copolymer		
108-65-6	2-methoxy-1-methylethyl acetate		
111-66-0	oct-1-ene		
· Standard for the Uniform Scheduling of Medicines and Poisons			
1330-20-7	xylene, mixture of isomers	S6	

#### · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms





# · Signal word Warning

### · Hazard-determining components of labelling:

xylene, mixture of isomers

Barium octoate

ethyl acrylate-2-ehtylhexyl acrylate copolymer

#### **Hazard statements**

Flammable liquid and vapour.

Harmful if inhaled.

Causes skin irritation.

Causes serious eve irritation.

### · Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical/ventilating/lighting/equipment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### · Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

(Contd. on page 10)





Vers.-Nr: 56 Revision: 23.05.2023

Trade name: Transolac Finish QD 3.33

(Contd. of page 9)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Flam. Liq. 4: Flammable liquids, Hazard Category 4

Acute Tox. 3: Acute toxicity, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

· \* Data compared to the previous version altered.

Αl