



Vers.-Nr: 44 Revision: 23.05.2023

Hazardous according to criteria of Australian Safety and Compensation Council.

#### 1 Identification

· Product identifier

· Trade name: Transocean Special Thinner 6.01

· Article number: 601 · CAS Number: 1330-20-7 · EC number: 215-535-7 · Index number:

· Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance/preparation:

Thinner, Diluent

601-022-00-9

Paint

· Details of the supplier of the safety data sheet

· Manufacturer/supplier:

Transocean Coatings

Wagon Paints Australia Pty Ltd

ABN: 76 412 791 772

Street address: 5 Stephenson Road, Bayswater North

VIC, 3153 Australia Phone: +613 9729-1344 Fax: +613 9720 2719

· Emergency telephone number:

· Medical Emergencies: 24 Hours

· Poisons Information Centre (Australia): 131 126

### 2 Hazard(s) Identification

· Classification of the substance or mixture

Flam. Liq. 3 H226 Flammable liquid and vapour. Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements

The substance is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms





GHS02 GHS07

(Contd. on page 2)





Vers.-Nr: 44 Revision: 23.05.2023

**Trade name: Transocean Special Thinner 6.01** 

(Contd. of page 1)

· Signal word Warning

· Hazard-determining components of labelling:

xylene, mixture of isomers

· Hazard statements

H226 Flammable liquid and vapour. H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

#### **3 Composition and Information on Ingredients**

· Chemical characterisation: Substances

· CAS No. Description

1330-20-7 xylene, mixture of isomers

- · Identification number(s)
- · EC number: 215-535-7
- · Index number: 601-022-00-9

#### **4 First Aid Measures**

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)





Vers.-Nr: 44 Revision: 23.05.2023

**Trade name: Transocean Special Thinner 6.01** 

(Contd. of page 2)

- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed
   No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### 5 Fire Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### **6 Accidental Release Measures**

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and Storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

#### 8 Exposure controls and personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)





Vers.-Nr: 44 Revision: 23.05.2023

**Trade name: Transocean Special Thinner 6.01** 

(Contd. of page 3)

#### · Control parameters

· Control p	· Control parameters					
· Ingredier	· Ingredients with limit values that require monitoring at the workplace:					
1330-20-7	1330-20-7 xylene, mixture of isomers					
			5 mg/m³, 150 ppm			
Lor	ng-term	n value: 350 mg/m³, 80 ppm				
· DNELs	· DNELs					
1330-20-7 xylene, mixture of isomers						
Dermal	long term DNEL		108 mg/kg/d (General Population)			
			180 mg/kg/d (Workers)			
Inhalative	Inhalative long term DNEL		14.8 mg/m3 (General Population)			
			77 mg/m3 (Workers)			
·PNECs						
1330-20-7	1330-20-7 xylene, mixture of isomers					
PNEC STP 6.58 mg/l		6.58 mg/l (	(water treatment plant)			
PNEC aqua 327 ug/l (f		327 ug/l (f	reshwater)			
327		327 ug/l (n	327 ug/l (marine water)			
PNEC sec	diment	12.46 mg/kg (freshwater)				
			kg (marine water)			

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls

PNEC soil

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

2.31 mg/kg (Soil)

Avoid contact with the skin.

Avoid contact with the eyes and skin.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

(Contd. on page 5)





Vers.-Nr: 44 Revision: 23.05.2023

**Trade name: Transocean Special Thinner 6.01** 

(Contd. of page 4)

#### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

General Information Appearance: Form: Colour: Colour: Colour: Odour: Not determined.  PH-value: Not determined.  Change in condition Melting point/freezing point: Initial boiling point and boiling range: 137-143 °C  Flash point: 25 °C  Flammability (solid, gas): Not applicable.  Ignition temperature: 500 °C  Decomposition temperature: Not determined.  Auto-ignition temperature: Not determined.  Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits: Lower: Upper: 1.1 Vol % Upper: 7 Vol %  Vapour pressure at 20 °C: 0.87 g/cm³ Relative density Not determined.  Not determined.  Solubility in / Miscibility with vater at 20 °C: 0.2 g/l  Partition coefficient: n-octanol/water: Not determined.	Information on basic physical and che	emical properties	
Form: Colour: Colouriess Odour: Aromatic Not determined.  PH-value: Not determined.  Change in condition Melting point/freezing point: 137-143 °C  Flash point: 25 °C  Flammability (solid, gas): Not applicable.  Ignition temperature: 500 °C  Decomposition temperature: Not determined.  Auto-ignition temperature: Not determined.  Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits: Lower: 1.1 Vol % Upper: 7 Vol %  Vapour pressure at 20 °C: 6.7-8.2 hPa  Density at 20 °C: 0.87 g/cm³ Not determined.  Possity at 20 °C: 0.87 g/cm³ Not determined.  Solubility in / Miscibility with water at 20 °C: 0.2 g/l  Partition coefficient: n-octanol/water: Not determined.  Viscosity: Dynamic at 20 °C: 0.61 mPas	General Information		
Colour: Odour Aromatic Odour threshold: Not determined.  PH-value: Not determined.  Change in condition Melting point/freezing point: Initial boiling point and boiling range: 137-143 °C  Flash point: 25 °C  Flammability (solid, gas): Not applicable.  Ignition temperature: Decomposition temperature: Not determined.  Auto-ignition temperature: Not determined.  Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits: Lower: Upper: 1.1 Vol % 7 Vol %  Vapour pressure at 20 °C: Relative density Not determined.  Partition coefficient: n-octanol/water: Not determined.	Appearance:		
Odour: Aromatic Not determined.  pH-value: Not determined.  Change in condition Melting point/freezing point: -34 °C Initial boiling point and boiling range: 137-143 °C  Flash point: 25 °C  Flammability (solid, gas): Not applicable.  Ignition temperature: 500 °C  Decomposition temperature: Not determined.  Auto-ignition temperature: Not determined.  Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits: 1.1 Vol % 7 Vol %  Vapour pressure at 20 °C: 6.7-8.2 hPa  Density at 20 °C: 0.87 g/cm³ Relative density Not determined.  Vapour density Not determined.  Solubility in / Miscibility with water at 20 °C: 0.2 g/l  Partition coefficient: n-octanol/water: Not determined.  Viscosity: Dynamic at 20 °C: 0.61 mPas	Form:		
Odour threshold: Not determined.  pH-value: Not determined.  Change in condition Melting point/freezing point: -34 °C Initial boiling point and boiling range: 137-143 °C  Flash point: 25 °C  Flammability (solid, gas): Not applicable.  Ignition temperature: 500 °C  Decomposition temperature: Not determined.  Auto-ignition temperature: Not determined.  Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits:  Lower: 1.1 Vol %			
PH-value: Not determined.  Change in condition Melting point/freezing point: 137-143 °C Initial boiling point and boiling range: 137-143 °C  Flash point: 25 °C  Flammability (solid, gas): Not applicable.  Ignition temperature: 500 °C  Decomposition temperature: Not determined.  Auto-ignition temperature: Not determined.  Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits:  Lower: 1.1 Vol % Upper: 7 Vol %  Vapour pressure at 20 °C: 6.7-8.2 hPa  Density at 20 °C: 0.87 g/cm³ Relative density Not determined.  Vapour density Not determined.  Solubility in / Miscibility with water at 20 °C: 0.2 g/l  Partition coefficient: n-octanol/water: Not determined.  Viscosity: Dynamic at 20 °C: 0.61 mPas	0.0.0	7 11 0 11 10 11 10	
Change in condition Melting point/freezing point: -34 °C Initial boiling point and boiling range: 137-143 °C  Flash point: 25 °C  Flammability (solid, gas): Not applicable.  Ignition temperature: 500 °C  Decomposition temperature: Not determined.  Auto-ignition temperature: Not determined.  Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits:  Lower: 1.1 Vol % Upper: 7 Vol %  Vapour pressure at 20 °C: 6.7-8.2 hPa  Density at 20 °C: 0.87 g/cm³ Relative density Not determined. Vapour density Not determined. Vapour density Not determined. Solubility in / Miscibility with water at 20 °C: 0.2 g/I  Partition coefficient: n-octanol/water: Not determined.  Viscosity: Dynamic at 20 °C: 0.61 mPas	Odour threshold:	Not determined.	
Melting point/freezing point: Initial boiling point and boiling range: 137-143 °C  Flash point: 25 °C  Flammability (solid, gas): Not applicable.  Ignition temperature: 500 °C  Decomposition temperature: Not determined.  Auto-ignition temperature: Not determined.  Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits: Lower: 1.1 Vol % 7 Vol %  Vapour pressure at 20 °C: 6.7-8.2 hPa  Density at 20 °C: 0.87 g/cm³ Not determined.  Vapour density Not determined.  Vapour density Not determined.  Solubility in / Miscibility with water at 20 °C: 0.2 g/l  Partition coefficient: n-octanol/water: Not determined.  Viscosity: Dynamic at 20 °C: 0.61 mPas	pH-value:	Not determined.	
Initial boiling point and boiling range: 137-143 °C  Flash point: 25 °C  Flammability (solid, gas): Not applicable.  Ignition temperature: 500 °C  Decomposition temperature: Not determined.  Auto-ignition temperature: Not determined.  Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits:  Lower: 1.1 Vol %			
Flash point: 25 °C  Flammability (solid, gas): Not applicable.  Ignition temperature: 500 °C  Decomposition temperature: Not determined.  Auto-ignition temperature: Not determined.  Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits:  Lower: 1.1 Vol %			
Flammability (solid, gas):  Not applicable.  Ignition temperature:  Decomposition temperature:  Not determined.  Auto-ignition temperature:  Not determined.  Explosive properties:  Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits:  Lower:  Upper:  1.1 Vol % 7 Vol %  Vapour pressure at 20 °C:  0.87 g/cm³ Relative density Not determined. Vapour density Not determined.  Not determined. Solubility in / Miscibility with water at 20 °C:  Partition coefficient: n-octanol/water:  Not determined.  Viscosity: Dynamic at 20 °C:  0.61 mPas	<u> </u>		
Ignition temperature:  Decomposition temperature:  Not determined.  Auto-ignition temperature:  Not determined.  Explosive properties:  Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits: Lower: Upper:  1.1 Vol % Upper:  7 Vol %  Vapour pressure at 20 °C: 6.7-8.2 hPa  Density at 20 °C: 6.7-8.2 hPa  Density at 20 °C: 0.87 g/cm³ Not determined. Vapour density Not determined. Not determined. Solubility in / Miscibility with water at 20 °C: 0.2 g/l  Partition coefficient: n-octanol/water: Not determined.  Viscosity: Dynamic at 20 °C: 0.61 mPas	Flash point:	25 °C	
Decomposition temperature:  Auto-ignition temperature:  Not determined.  Explosive properties:  Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits:  Lower:  Upper:  1.1 Vol % 7 Vol %  Vapour pressure at 20 °C:  6.7-8.2 hPa  Density at 20 °C:  0.87 g/cm³ Not determined. Vapour density Not determined. Vapour density Not determined. Solubility in / Miscibility with water at 20 °C:  Partition coefficient: n-octanol/water:  Not determined.  Viscosity: Dynamic at 20 °C:  0.61 mPas	Flammability (solid, gas):	Not applicable.	
Auto-ignition temperature:  Explosive properties:  Product is not explosive. However, formation of explosive air/vapour mixtures are possible.  Explosion limits:  Lower: Upper:  1.1 Vol % 7 Vol %  Vapour pressure at 20 °C:  6.7-8.2 hPa  Density at 20 °C:  Relative density Vapour density Not determined. Vapour density Not determined. Solubility in / Miscibility with water at 20 °C:  Partition coefficient: n-octanol/water: Not determined.  Viscosity: Dynamic at 20 °C:  0.61 mPas	Ignition temperature:	500 °C	
Explosive properties:  Explosion limits:  Lower: Upper:  Vapour pressure at 20 °C:  Relative density Vapour density Vapour density Vapour density Not determined.  Solubility in / Miscibility with water at 20 °C:  Partition coefficient: n-octanol/water: Not determined.  Viscosity: Dynamic at 20 °C:  0.61 mPas	Decomposition temperature:	Not determined.	
explosive air/vapour mixtures are possible.  Explosion limits: Lower: Upper: 1.1 Vol % 7 Vol %  Vapour pressure at 20 °C: 6.7-8.2 hPa  Density at 20 °C: 0.87 g/cm³ Not determined. Vapour density Not determined. Evaporation rate Not determined. Solubility in / Miscibility with water at 20 °C: 0.2 g/l  Partition coefficient: n-octanol/water: Not determined.  Viscosity: Dynamic at 20 °C: 0.61 mPas	Auto-ignition temperature:	Not determined.	
Lower: Upper: 7 Vol % 7 Vol %  Vapour pressure at 20 °C: 6.7-8.2 hPa  Density at 20 °C: 0.87 g/cm³ Not determined. Vapour density Not determined. Evaporation rate Not determined. Solubility in / Miscibility with water at 20 °C: 0.2 g/l  Partition coefficient: n-octanol/water: Not determined.	Explosive properties:		
Upper: 7 Vol %  Vapour pressure at 20 °C: 6.7-8.2 hPa  Density at 20 °C: 0.87 g/cm³ Relative density Not determined. Vapour density Not determined. Evaporation rate Not determined.  Solubility in / Miscibility with water at 20 °C: 0.2 g/l  Partition coefficient: n-octanol/water: Not determined.  Viscosity: Dynamic at 20 °C: 0.61 mPas	Explosion limits:		
Vapour pressure at 20 °C:  Density at 20 °C:  Relative density  Vapour density  Vapour density  Evaporation rate  Solubility in / Miscibility with water at 20 °C:  Partition coefficient: n-octanol/water:  Not determined.  Not determined.  0.2 g/l  Partition coefficient: n-octanol/water:  Not determined.	Lower:	111 1 41 14	
Density at 20 °C: Relative density Vapour density Not determined. Vaporation rate Not determined. Solubility in / Miscibility with water at 20 °C:  Partition coefficient: n-octanol/water: Not determined.  Viscosity: Dynamic at 20 °C:  0.87 g/cm³ Not determined.  Not determined.	Upper:	7 Vol %	
Relative density Vapour density Evaporation rate  Solubility in / Miscibility with water at 20 °C:  Partition coefficient: n-octanol/water: Not determined.  Not determined.  0.2 g/l  Partition coefficient: n-octanol/water: Not determined.  Viscosity: Dynamic at 20 °C:  0.61 mPas	Vapour pressure at 20 °C:	6.7-8.2 hPa	
Vapour density Evaporation rate  Not determined. Not determined.  Solubility in / Miscibility with water at 20 °C:  Partition coefficient: n-octanol/water: Not determined.  Viscosity: Dynamic at 20 °C:  0.61 mPas		0.87 g/cm <sup>3</sup>	
Evaporation rate  Not determined.  Solubility in / Miscibility with water at 20 °C:  Partition coefficient: n-octanol/water:  Not determined.  Viscosity: Dynamic at 20 °C:  0.61 mPas			
Solubility in / Miscibility with water at 20 °C:  Partition coefficient: n-octanol/water:  Not determined.  Viscosity:  Dynamic at 20 °C:  0.2 g/l  0.2 g/l  0.61 mPas			
water at 20 °C:  Partition coefficient: n-octanol/water:  Not determined.  Viscosity:  Dynamic at 20 °C:  0.61 mPas	· Evaporation rate	Not determined.	
Partition coefficient: n-octanol/water: Not determined.  Viscosity: Dynamic at 20 °C: 0.61 mPas			
Viscosity: Dynamic at 20 °C: 0.61 mPas	water at 20 °C:	0.2 g/l	
Dynamic at 20 °C: 0.61 mPas	Partition coefficient: n-octanol/water:	Not determined.	
	· Viscosity:		

(Contd. on page 5)





Vers.-Nr: 44 Revision: 23.05.2023

Trade name: Transocean Special Thinner 6.01

(Contd. of page 5)

	(contained page
VOC (EC)	870.0 g/l
· Other information	No further relevant information available.

### 10 Stability and Reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological Information

- · Information on toxicological effects
- Acute toxicity

<ul> <li>LD/LC50 values relevant for classificat</li> </ul>	ion.	lassificat	for cl	relevant	values	D/I C50	· I
---	------	------------	--------	----------	--------	---------	-----

1330-20-7	1330-20-7 xylene, mixture of isomers				
Oral	LD50	>2000 mg/kg (rat)			
	LC50/ 96 hr (static)	2.6 mg/l (Rainbow trout (Oncorhynchus mykiss)) (OESO 203 or equivalent)			
Dermal	LD50	>2000 mg/kg (rabbit)			
Inhalative	LC50/4 h	>20 mg/l (rat)			

- · Primary irritant effect:
- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.

#### **12 Ecological Information**

· Toxicity

· Aquatic toxicity:

#### 1330-20-7 xylene, mixture of isomers

EC 50 (48 hr) | 1-10 mg/l (daphnia) EC 50 (72 hr) | 1-10 mg/l (Algae)

- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Assessment by list): hazardous for water Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 7)





Vers.-Nr: 44 Revision: 23.05.2023

Trade name: Transocean Special Thinner 6.01

(Contd. of page 6)

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information	
· UN-Number · ADG, IMDG, IATA	UN1307
<ul><li>UN proper shipping name</li><li>ADG</li><li>IMDG, IATA</li></ul>	1307 XYLENES XYLENES
<ul><li>Transport hazard class(es)</li><li>ADG, IMDG, IATA</li></ul>	
· Class · Label	3 Flammable liquids.
· Packing group · ADG, IMDG, IATA	III
<ul><li>Environmental hazards:</li><li>Marine pollutant:</li></ul>	No
<ul> <li>Special precautions for user</li> <li>Hazard identification number (Kemler code):</li> <li>EMS Number:</li> <li>Stowage Category</li> </ul>	Warning: Flammable liquids. 30 F-E,S-D A
<ul> <li>Transport in bulk according to Annex II of Marpol and the IBC Code</li> </ul>	Not applicable.
· Transport/Additional information:	
<ul><li>ADG</li><li>Limited quantities (LQ)</li><li>Excepted quantities (EQ)</li></ul>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml
· Transport/Additional information: · ADG · Limited quantities (LQ)	5L Code: E1

Contd. on page 7





Vers.-Nr: 44 Revision: 23.05.2023

**Trade name: Transocean Special Thinner 6.01** 

	(Contd. of page 7)
· · Transport category · Tunnel restriction code	Maximum net quantity per outer packaging: 1000 ml 3 D/E
IMDG     Limited quantities (LQ)     Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1307 XYLENES, 3, III

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or
- · Australian Inventory of Industrial Chemicals

Substance is listed.

· Standard for the Uniform Scheduling of Medicines and Poisons

S6

· Australia: Priority Existing Chemicals

Substance is not listed.

· GHS label elements

The substance is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

xylene, mixture of isomers

· Hazard statements

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

(Contd. on page 9)





Vers.-Nr: 44 Revision: 23.05.2023

Trade name: Transocean Special Thinner 6.01

(Contd. of page 8)

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I Substance is not listed.

· Seveso category P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Contact:

#### Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - dermal - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

· \* Data compared to the previous version altered.

AU