

Safety data sheet according to WHS Regulations

Vers.-Nr: 50


Revision: 23.05.2023

Hazardous according to criteria of Australian Safety and Compensation Council

1 Identification

- **Product identifier**
- **Trade name:** Transocean PU Thinner 6.04
- **Article number:** 604
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance/preparation:**
Thinner, Diluent
Paint
- **Details of the supplier of the safety data sheet**
- **Manufacturer/supplier:**
Transocean Coatings
Wagon Paints Australia Pty Ltd
ABN: 76 412 791 772
Street address: 5 Stephenson Road, Bayswater North
VIC, 3153 Australia
Phone: +613 9729-1344
Fax: +613 9720 2719
- **Emergency telephone number:**
- Medical Emergencies: 24 Hours
- Poisons Information Centre (Australia): 131 126

2 Hazard Identification

- **Classification of the substance or mixture**
Flam. Liq. 3 H226 Flammable liquid and vapour.
Skin Irrit. 2 H315 Causes skin irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.
- **Label elements**
- **GHS label elements**
The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**

GHS02 GHS07
- **Signal word** Warning
- **Hazard-determining components of labelling:**
xylene, mixture of isomers
- **Hazard statements**
Flammable liquid and vapour.
Causes skin irritation.
May cause drowsiness or dizziness.
- **Precautionary statements**
If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

AU

Safety data sheet according to WHS Regulations

Vers.-Nr: 50

Revision: 23.05.2023

Trade name: Transocean PU Thinner 6.04

(Contd. of page 1)

- Keep out of reach of children.
- Read label before use.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- Specific treatment (see on this label).
- Store locked up.
- Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

* 3 Composition and information on ingredients

- **Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

123-86-4	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	50-100%
1330-20-7	xylene, mixture of isomers Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	25-50%
108-65-6	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	10-25%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

* 4 First Aid Measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

AU
(Contd. on page 3)

Safety data sheet according to WHS Regulations

Vers.-Nr: 50

Revision: 23.05.2023

Trade name: Transocean PU Thinner 6.04

(Contd. of page 2)

5 Fire Fighting Measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 4)

Safety data sheet according to WHS Regulations

Vers.-Nr: 50

Revision: 23.05.2023

Trade name: Transocean PU Thinner 6.04

(Contd. of page 3)

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

123-86-4 n-butyl acetate

NES	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 713 mg/m ³ , 150 ppm
-----	---

1330-20-7 xylene, mixture of isomers

NES	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 350 mg/m ³ , 80 ppm
-----	--

108-65-6 2-methoxy-1-methylethyl acetate

NES	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
-----	--

· **DNELs**

1330-20-7 xylene, mixture of isomers

Dermal	long term DNEL	108 mg/kg/d (General Population)
		180 mg/kg/d (Workers)
Inhalative	long term DNEL	14.8 mg/m ³ (General Population)
		77 mg/m ³ (Workers)

· **PNECs**

1330-20-7 xylene, mixture of isomers

PNEC STP	6.58 mg/l (water treatment plant)
PNEC aqua	327 ug/l (freshwater)
	327 ug/l (marine water)
PNEC sediment	12.46 mg/kg (freshwater)
	12.46 mg/kg (marine water)
PNEC soil	2.31 mg/kg (Soil)

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

AU

Safety data sheet according to WHS Regulations

Vers.-Nr: 50

Revision: 23.05.2023

Trade name: Transocean PU Thinner 6.04

(Contd. of page 4)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

<ul style="list-style-type: none"> · Information on basic physical and chemical properties · General Information · Appearance: <li style="padding-left: 20px;">Form: Fluid <li style="padding-left: 20px;">Colour: According to product specification · Odour: Characteristic · Odour threshold: Not determined. 	
· pH-value:	Not determined.
· Change in condition	
Boiling point/Boiling range:	124 °C
· Flash point:	27 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	315 °C
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	10.8 Vol %
· Vapour pressure at 20 °C:	10.7 hPa
· Density at 20 °C:	0.89272 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

(Contd. on page 6)

AU

Safety data sheet according to WHS Regulations

Vers.-Nr: 50

Revision: 23.05.2023

Trade name: Transocean PU Thinner 6.04

(Contd. of page 4)

· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	11 s (DIN 53211/4)
· Solvent content:	
VOC (EC)	892.7 g/l
· Other information	No further relevant information available.

* 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

* 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

- **LD/LC50 values relevant for classification:**

1330-20-7 xylene, mixture of isomers

Oral	LD50	>2000 mg/kg (rat)
	LC50/ 96 hr (static)	2.6 mg/l (Rainbow trout (<i>Oncorhynchus mykiss</i>)) (OESO 203 or equivalent)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>20 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Irritant to skin and mucous membranes.
- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.

- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful
Irritant

AU

(Contd. on page 7)

Safety data sheet according to WHS Regulations

Vers.-Nr: 50

Revision: 23.05.2023

Trade name: Transocean PU Thinner 6.04

(Contd. of page 4)

* 12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

1330-20-7 xylene, mixture of isomers

EC 50 (48 hr) 1-10 mg/l (daphnia)

EC 50 (72 hr) 1-10 mg/l (Algae)

· **Persistence and degradability** No further relevant information available.

· **Behaviour in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

* 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

* 14 Transport information

· **UN-Number**

· **ADG, IMDG, IATA**

UN1993

· **UN proper shipping name**

· **ADG**

1993 FLAMMABLE LIQUID, N.O.S. (BUTYL ACETATES, XYLENES), special provision 640E
FLAMMABLE LIQUID, N.O.S. (BUTYL ACETATES, XYLENES)

· **IMDG**

· **IATA**

Flammable liquid, n.o.s. (Butyl acetates, Xylenes)

(Contd. on page 8)


Safety data sheet according to WHS Regulations

Vers.-Nr: 50

Revision: 23.05.2023

Trade name: Transocean PU Thinner 6.04

(Contd. of page 4)

<ul style="list-style-type: none"> · Transport hazard class(es) · ADG, IMDG, IATA 	<div style="text-align: center;">  </div>
<ul style="list-style-type: none"> · Class · Label 	<p>3 Flammable liquids. 3</p>
<ul style="list-style-type: none"> · Packing group · ADG, IMDG, IATA 	<p>III</p>
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: 	<p>No</p>
<ul style="list-style-type: none"> · Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category 	<p>Warning: Flammable liquids. 30 F-E,<u>S-E</u> A</p>
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of Marpol and the IBC Code 	<p>Not applicable.</p>
<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · ADG · Limited quantities (LQ) · Excepted quantities (EQ) 	<p>5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml</p>
<ul style="list-style-type: none"> · Transport category · Tunnel restriction code 	<p>3 D/E</p>
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	<p>5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml</p>
<ul style="list-style-type: none"> · UN "Model Regulation": 	<p>UN 1993 FLAMMABLE LIQUID, N.O.S., SPECIAL PROVISION 640E (BUTYL ACETATES, XYLENES), 3, III</p>

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Chemical Substances

All ingredients are listed.

· Standard for the Uniform Scheduling of Medicines and Poisons

1330-20-7 xylene, mixture of isomers

S6

(Contd. on page 9)

Safety data sheet according to WHS Regulations

Vers.-Nr: 50

Revision: 23.05.2023

Trade name: Transocean PU Thinner 6.04

(Contd. of page 4)

- **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning

- **Hazard-determining components of labelling:**

xylene, mixture of isomers

- **Hazard statements**

Flammable liquid and vapour.

Causes skin irritation.

May cause drowsiness or dizziness.

- **Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

- **Seveso category** P5c FLAMMABLE LIQUIDS

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(Contd. on page 10)

AU

Safety data sheet according to WHS Regulations

Vers.-Nr: 50

Revision: 23.05.2023

Trade name: Transocean PU Thinner 6.04

(Contd. of page 9)

PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids, Hazard Category 3
Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
• *** Data compared to the previous version altered.**

AU