

Page 1/10

Safety Data Sheet according to WHS Regulations

Vers.-Nr: 51

Revision: 23.05.2023

Hazardous according to criteria of Australian Safety and Compensation Council.

1 Identification

- · Product identifier
- · Trade name: Transpoxy Guard 4.75 Pack A
- · Article number: 9464-7100-a
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- Application of the substance/preparation: Epoxy coating Paint
- · Details of the supplier of the safety data sheet
- Manufacturer/supplier: Transocean Coatings Wagon Paints Australia Pty Ltd ABN: 76 412 791 772 Street address: 5 Stephenson Road, Bayswater North VIC, 3153 Australia Phone: +613 9729-1344 Fax: +613 9720 2719 Emergence telephone number:
- Emergency telephone number:
- · Medical Emergencies: 24 Hours
- Poisons Information Centre (Australia): 131 126

2 Hazard(s) Identification

· Classification of the substance or mixture

- Flam. Liq. 3H226Flammable liquid and vapour.Skin Irrit. 2H315Causes skin irritation.Eye Irrit. 2AH319Causes serious eye irritation.Skin Sens. 1H317May cause an allergic skin reaction.Repr. 1BH360D May damage the unborn child.
- · Label elements
- · GHS label elements
- The product is classified and labelled according to the Globally Harmonised System (GHS).
- Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

reaction product of bisphenol-F-epichlorhydrin oxirane, mono[(C12-14-alkyloxy)methyl] derivs

(Contd. on page 2)

AU



Safety Data Sheet according to WHS Regulations

Vers.-Nr: 51

Revision: 23.05.2023

	(Contd. of page
· Hazard statements	(00.1121 01 9490
Flammable liquid and vapour.	
Causes skin irritation.	
Causes serious eye irritation.	
May cause an allergic skin reaction.	
May damage the unborn child.	
Precautionary statements	
Keep away from heat/sparks/open flames/hot surfaces. No smoking.	
Use explosion-proof electrical/ventilating/lighting equipment.	
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Ri shower.	nse skin with water/
IF IN EYES: Rinse cautiously with water for several minutes. Remove c and easy to do. Continue rinsing.	ontact lenses, if present
Store locked up. Dispose of contents/container in accordance with local/regional/national	/international regulations
• Other hazards	/international regulations.
Results of PBT and vPvB assessment	
• PBT: Not applicable.	
• vPvB: Not applicable.	

· Dangerous	components:	
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)	10-25%
	🍄 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	
28064-14-4	reaction product of bisphenol-F-epichlorhydrin	10-25%
	🍄 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	
68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs	2.5-10%
	🍄 Skin Irrit. 2, H315; Skin Sens. 1, H317	
78-83-1	iso-butanol	2.5%
	🧇 Flam. Liq. 3, H226; Eye Dam. 1, H318; 🚸 Skin Irrit. 2, H315; STOT	
	SE 3, H335-H336	
872-50-4	N-methyl-2-pyrrolidone	2.5%
	Kepř. 18, H360D; () SKIN IIII. 2, H315; Eye IIII. 2A, H319; STOT SE 3,	
	H335; Flam. Liq. 4, H227	
· SVHC		

872-50-4 N-methyl-2-pyrrolidone

• Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

· Description of first aid measures

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 2)

AU



Safety Data Sheet according to WHS Regulations

Vers.-Nr: 51

Revision: 23.05.2023

Trade name: Transpoxy Guard 4.75 Pack A

· After eye contact:

(Contd. of page 2)

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • After swallowing: If symptoms persist consult doctor.

- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- \cdot Special hazards arising from the substance or mixture
- No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental Release Measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection:
 Keep ignition sources away Do not smoke.
 Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

(Contd. on page 4)



according to WHS Regulations

Vers.-Nr: 51

Revision: 23.05.2023

(Contd. of page 3)

Trade name: Transpoxy Guard 4.75 Pack A

· Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· Control parameters

· Ingredients with limit values that require monitoring at the workplace:

78-83-1 iso-butanol

WES Long-term value: 152 mg/m³, 50 ppm

872-50-4 N-methyl-2-pyrrolidone

WES Short-term value: 309 mg/m³, 75 ppm Long-term value: 103 mg/m³, 25 ppm Sk

• Additional information: The lists valid during the making were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.
- Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)



Safety Data Sheet according to WHS Regulations

Vers.-Nr: 51

Revision: 23.05.2023

Trade name: Transpoxy Guard 4.75 Pack A

(Contd. of page 4)

· Eye protection:



Tightly sealed goggles

· Information on basic physical and chem	ical properties
· General Information	
Appearance:	
Form:	Fluid
Colour: · Odour:	According to product specification Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
•	
 Change in condition Melting point/freezing point: 	Undetermined.
Initial boiling point and boiling range:	Undetermined.
· Flash point:	>25 °C
 Flammability (solid, gas): 	Not applicable.
 Ignition temperature: 	> 300 °C
· Decomposition temperature:	Not determined.
 Auto-ignition temperature: 	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density at 20 °C:	1.72174 g/cm ³
Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
VOC (EC)	41.3 g/l
	(Contd. on page



Page 6/10

Safety Data Sheet according to WHS Regulations

Vers -Nr: 51

Revision: 23.05.2023

(Contd. of page 5)

Trade name: Transpoxy Guard 4.75 Pack A

· Other information

No further relevant information available.

10 Stability and Reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity
- · LD/LC50 values relevant for classification:

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average
molecular weight = 700)OralLD50>5000 mg/kg (rat)

 Oral
 LD50
 >5000 mg/kg (rat)

 LC50/ 96 hr
 1.5 mg/l (fish)

 Dermal
 LD50
 >2000 mg/kg (rat)

Primary irritant effect:

- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Serious eye damage/irritation Irritating effect.
- · Respiratory or skin sensitisation Sensitisation possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

12 Ecological Information

- · Toxicity
- Aquatic toxicity:

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average
molecular weight = 700)EC 50 (48 hr)1.7 mg/l (daphnia)EC 50 (72 hr)9.4 mg/l (Algae)



Trade name: Transpoxy Guard 4.75 Pack A

· Additional ecological information:

· General notes:

Safety Data Sheet according to WHS Regulations

Vers.-Nr: 51

Revision: 23.05.2023

(Contd. of page 6)

Also poisonous for fish and plank	ound water, water course or sewage system. small quantities leak into the ground. ton in water bodies.
Toxic for aquatic organisms • Results of PBT and vPvB asses	ssment
 • PBT: Not applicable. • vPvB: Not applicable. 	
• Other adverse effects No furthe	r relevant information available.
3 Disposal considerations	
-	
 Waste treatment methods Recommendation 	
Must not be disposed together wi system.	th household garbage. Do not allow product to reach sewage
Uncleaned packaging:	
Recommendation: Disposal must	st be made according to official regulations.
Transport information	
Transport information	
Transport information UN-Number ADG, IMDG, IATA	UN1263
 UN-Number ADG, IMDG, IATA UN proper shipping name 	
· UN-Number · ADG, IMDG, IATA	UN1263 1263 PAINT, ENVIRONMENTALLY HAZARDOU special provision 640E
 UN-Number ADG, IMDG, IATA UN proper shipping name 	1263 PAINT, ENVIRONMENTALLY HAZARDOU special provision 640E PAI NT (r eacti on pr oduct of bi sphenol -
 UN-Number ADG, IMDG, IATA UN proper shipping name ADG 	1263 PAINT, ENVIRONMENTALLY HAZARDOU special provision 640E PAI NT (reacti on product of bi sphenol - epichlorhydrin, reaction product: bisphenol (epichlorhydrin) epoxy resin (number avera
 UN-Number ADG, IMDG, IATA UN proper shipping name ADG 	1263 PAINT, ENVIRONMENTALLY HAZARDOU special provision 640E PAI NT (r eacti on pr oduct of bi sphenol - epichlorhydrin, reaction product: bisphenol
 UN-Number ADG, IMDG, IATA UN proper shipping name ADG IMDG 	1263 PAINT, ENVIRONMENTALLY HAZARDOU special provision 640E PAI NT (r eacti on pr oduct of bi sphenol - epichlorhydrin, reaction product: bisphenol (epichlorhydrin) epoxy resin (number avera molecular weight = 700)), MARINE POLLUTANT
 UN-Number ADG, IMDG, IATA UN proper shipping name ADG IMDG IATA 	1263 PAINT, ENVIRONMENTALLY HAZARDOU special provision 640E PAI NT (r eacti on pr oduct of bi sphenol - epichlorhydrin, reaction product: bisphenol (epichlorhydrin) epoxy resin (number avera molecular weight = 700)), MARINE POLLUTANT
 UN-Number ADG, IMDG, IATA UN proper shipping name ADG IMDG IATA Transport hazard class(es) 	1263 PAINT, ENVIRONMENTALLY HAZARDOU special provision 640E PAI NT (r eacti on pr oduct of bi sphenol - epichlorhydrin, reaction product: bisphenol (epichlorhydrin) epoxy resin (number avera molecular weight = 700)), MARINE POLLUTANT
 UN-Number ADG, IMDG, IATA UN proper shipping name ADG IMDG IATA Transport hazard class(es) 	1263 PAINT, ENVIRONMENTALLY HAZARDOU special provision 640E PAI NT (r eacti on pr oduct of bi sphenol - epichlorhydrin, reaction product: bisphenol (epichlorhydrin) epoxy resin (number avera molecular weight = 700)), MARINE POLLUTANT



Safety Data Sheet according to WHS Regulations

Vers.-Nr: 51

Revision: 23.05.2023

ade name: Transpoxy Guard 4.75 Pack A		
	(Contd. of page 6)	
· Class · Label	3 Flammable liquids. 3	
 Packing group ADG, IMDG, IATA 	111	
 Environmental hazards: Marine pollutant: 	Product contains environmentally hazardous substances: Yes Symbol (fish and tree)	
· Special marking (ADG):	Symbol (fish and tree)	
 Special precautions for user Danger code (Kemler): EMS Number: Stowage Category 	Warning: Flammable liquids. 30 F-E <u>,S-E</u> A	
 Transport in bulk according to Annex II Marpol and the IBC Code 	of Not applicable.	
· Transport/Additional information:		
 ADG Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 D/E	
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml	
· UN "Model Regulation":	UN 1263 PAINT, SPECIAL PROVISION 640E, 3, III, ENVIRONMENTALLY HAZARDOUS	

15 Regulatory information

- \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture
- Australian Inventory of Chemical Substances
 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average
 molecular weight = 700)
 28064-14-4 reaction product of bisphenol-F-epichlorhydrin
 (Contd. on page 9)

AU



Safety Data Sheet according to WHS Regulations

Vers.-Nr: 51

Revision: 23.05.2023

Trade name: Transpoxy Guard 4.75 Pack A	
---	--

(Contd. of page 6)

AU

13463-67-7 titanium dioxide 14807-96-6 Talc (Mg3H2(SiO3)4) 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs 78-83-1 iso-butanol 8002-43-5 Soyalecithine 872-50-4 N-methyl-2-pyrrolidone 7447-41-8 lithium chloride · Standard for the Uniform Scheduling of Medicines and Poisons None of the ingredients is listed. · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS). Hazard pictograms GHS02 GHS07 GHS08 · Signal word Danger · Hazard-determining components of labelling: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700) reaction product of bisphenol-F-epichlorhydrin oxirane, mono[(C12-14-alkyloxy)methyl] derivs **Hazard statements** Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May damage the unborn child. **Precautionary statements** Keep away from heat/sparks/open flames/hot surfaces. No smoking. Use explosion-proof electrical/ventilating/lighting equipment. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. Directive 2012/18/EU · Named dangerous substances - ANNEX I None of the ingredients is listed. Seveso category E2 Hazardous to the Aquatic Environment P5c FLAMMABLE LIQUIDS · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t • Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t (Contd. on page 10)



Page 10/10

Safety Data Sheet according to WHS Regulations

Vers.-Nr: 51

Revision: 23.05.2023

Trade name: Transpoxy Guard 4.75 Pack A

(Contd. of page 9)

· National regulations:

· Other regulations, limitations and prohibitive regulations

· Substances of very high concern (SVHC) according to REACH, Article 57

872-50-4 N-methyl-2-pyrrolidone

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3 Flam. Liq. 4: Flammable liquids - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Skin Sens. 1: Skin sensitisation - Category 1 Repr. 1B: Reproductive toxicity - Category 1B STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 • * Data compared to the previous version altered.